



KAUKIT4

by Burndy Catalog ID: KAUKIT4

Prop65

Al Transformer Lug Kit, 500 kVA.

Features: These Dual-Rated Lugs Are Constructed From High Strength Aluminum Alloy And Electro Tinplated To Provide Low Contact Resistance, Lugs And Mounting Hardware Packaged Together In These Kits, UL Listed AL9CU Dual Rated Set Screw Terminals And CSA Certified, Ensure The Transformer Feeders And Taps Are Terminated Properly, Plated Steel Cap Screws And Hex Nuts With Captive Conical Washers Or Individual Belleville Washers, Terminal To Bus Connections Are Made Using Proper Hardware Resulting In True Torque To Pressure Performance, Compensates For Dissimilar Metal Expansion And Contraction, Hardware Packed In Plastic Bag, No Lost Hardware Prior To Installation, Conductor Type: Run: Stranded Aluminum Or Copper, Includes: (7) 1/2-13 X 2 IN, (4) 1/2-13 X 2-1/2 IN, (11) 1/2-13 Hex Head, (15) K2A40U Terminal, (11) 1/2 IN Belleville Washer, (22) 1/2 IN Flatwasher, Transformer Kva Rating Range: 400 - 500 KVA For Single Phase

Product Details

General

Application	used to provide low contact resistance
Material	Aluminum
Sub Brand	UNIVERSAL TERM
Туре	Bolted Lugs & Terminals
UPC	781810600146

Conductor Related

Conductor - AL Str Size	300 kcmil;336 kcmil;350 kcmil;397 kcmil;400 kcmil;450 kcmil;477 kcmil;500 kcmil;550 kcmil;556 kcmil;600 kcmil;636 kcmil;650 kcmil;700
	kcmil;715 kcmil;750 kcmil;795 kcmil;800 kcmil

Certifications and Compliance

Certification - CSA Approved	No
Certification - ETL	No
Certification - UL Listed Direct Burial	No
Certification - UL Recognized	No
Certification - cULus	No
Standards - RoHS Compliance Status	EX
UL Listed	No

Logistics

Minimum Pack Quantity	1
Package Contents	(15) K2A40U;(7) 1/2-13 x 2 in, (4) 1/2-13 x 2-1/2 in Hex Head Bolts;(11) 1/2-13 Hex Head Nuts;(22) 1/2 in Flat Washers;(11) 1/2 in Belleville Washers

BURNDY Headquarters

47 East Industrial Park Drive Manchester, New Hampshire 03109

Customer Service Hours:

8 AM - 8 PM Eastern Monday-Friday Emergency Service 24-hours/365 Days

Phone: 1-800-346-4175

1-603-647-5299 (International)