BURNDY®

KC26, SERVIT POST Mechanical Connector, Cable to Flat

By Burndy
Catalog # KC26

Mechanical SERVIT POST™ Connector; Cable to Flat

Features

- SERVIT POST™ mechanical connector used to ground 1 or 2 cables to steel structures, fence posts, and transformers
- Also used to tap 1 or 2 cables from bus bar
- 1-Wrench installation

Application

For Used To Ground One Or Two Copper Cables To Steel Structures, Fence Posts, Transformers, Tap One Or Two Cables From Bus Bar And Direct Burial

Specifications

Buy American Compliant	Contact Manufacturer
Certification - cULus	No
EU RoHS Indicator	Yes
Certification - UL Recognized	No
Industry Standard(s)	UL467
Buy America(n) Qualified	Contact Manufacturer
Certification - ETL	No
Standards - Industry Standards Met	UL467
Standards - RoHS Compliance Status	EX
Certification - CSA Approved	No
UL Listed	Yes
Certification - UL Listed Direct Burial	Yes

Conductor

Conductor - Copper Str Size	• 2 AWG • 1 AWG • 1/0 • 2/0 AWG
Conductor - Copper Solid Size	• 2 AWG • 1 AWG • 1/0 AWG • 2/0 AWG • 3/0 AWG
Conductor - Copper Solid Size Range	2 AWG-3/0 AWG
Conductor - Copper Str Size Range	2 AWG-2/0 AWG

Physical Attribute - Number of Conductors Accommodated Total — 1

Dimensions

Dimension - Nut Width inch	1.04 in
Dimension - P inch	0.44 in
Dimension - Height fraction	1-3/8
Dimension - Height mm	35.1 mm
Dimension - Threads per inch	13
Dimension - B Length fraction	17/32 in
Dimension - Body Width inch	0.88 in
Dimension - Bolt Size fraction	1/2
Dimension - Length Overall inch	2.12 in
Dimension - D inch	0.75 in

Force Related

Installation Torque Recommended in-lb	480 LBS/in
Stud Installation Torque inch pounds	480 LBS/in

General

Trade Name	SERVIT POST™
Sub Brand	SERVIT POST
Plated	N
Type	KC and K2C Series
UPC 12 Digit	781810255957
UPC 14 Digit GTIN	00781810255957
Material	Bronze, Leaded, Commercial
Plating Type	Unplated
UPC	781810255957

Logistics

Minimum Pack Quantity	1
Carton Quantity	25
Pallet Quantity	7425

Product Assets

Catalog [English]