

KPA4C, Mechanical Pressure Bar Style Copper Lug, 1-Hole, #14 AWG Sol-4 AWG Str, 1/4" Stud, 1 Screw

By Burndy
Catalog # [KPA4C](#)

Copper Terminal, 1 Hole, 14 AWG (Sol)-4 AWG (Str), 1/4" Stud, 1 Screw, Tin Plated



Features

- High copper alloy terminal (tin-plated) for joining a wide range of cable to equipment pads or terminal blocks
- Tongue and body are 1-piece design, pressure bar equalizes pressure over the conductor and prevents the screw from cutting into the cable

Application

For Joining A Wide Range Of Cable To Equipment Pads Or Terminal Blocks, Especially Good In Light Industrial Applications

Specifications

Buy American Compliant	No
Certification - cULus	No
EU RoHS Indicator	Yes
Certification - UL Recognized	No
Industry Standard(s)	UL 486A-486B
Certification - ETL	No
Standards - Industry Standards Met	UL 486A-486B
Standards - RoHS Compliance Status	CM
Certification - CSA Approved	Yes
UL Listed	Yes
Certification - UL Listed Direct Burial	No

Conductor

Conductor - Copper Str Size	<ul style="list-style-type: none"> • 14 AWG • 12 AWG • 10 AWG • 9 AWG • 8 AWG • 7 AWG • 6 AWG • 5 AWG • 4 AWG
Conductor - Copper Solid Size	<ul style="list-style-type: none"> • 14 AWG • 13 AWG • 12 AWG • 11 AWG • 10 AWG • 9 AWG • 8 AWG

- 7 AWG
- 6 AWG
- 5 AWG
- 4 AWG

Conductor - Copper Solid Size Range 14 AWG-4 AWG

Conductor - Copper Str Navy Size

- 23 (7) Navy
- 30 (19) Navy
- 40 (19) Navy

Conductor - Copper Str Navy Size Range 23 (7) Navy-40 (19) Navy

Conductor Size 14-4 AWG

Conductor - Copper Str Size Range 14 AWG-4 AWG

Conductor Type

- CU C Str-Size
- CU C Solid-Size

Configuration

Physical Attribute - Number of Holes 1

Physical Attribute - Number of Screws 1

Connector Type Pressure Bar

Dimensions

Dimension - L Length Overall mm	31 mm
Dimension - Pad Width inch	0.50 in
Dimension - Height fraction	47/50 in
Dimension - Height inch	0.94 in
Dimension - Height mm	23.9 mm
Dimension - Hole Size inch	0.27 in
Dimension - Hole Size mm	7 mm
Dimension - Stud Size inch	1/4
Dimension - Bolt Size fraction	1/4
Dimension - Length Overall inch	1.22 in
Dimension - D inch	0.59 in
Dimension - N inch	0.30 in

Force Related

Installation Torque Recommended in-lb 35 LBS/in

General

Trade Name	SCRULUG™
Sub Brand	SCRULUG
Physical Attribute - Screw Type	Slot
Plated	Y
Type	Bolted Lugs & Terminals
UPC 14 Digit GTIN	00781810351352
Material	Copper
Plating Type	Tin
UPC	781810351352

Logistics

Minimum Pack Quantity	1
Carton Quantity	100
Pallet Quantity	59400

Product Assets

[Catalog \[English\]](#)



A Hubbell brand