


KS15, Split Bolt Connector, Run/Tap: #10-8 AWG Str

By Burndy
Catalog # [KS15](#)

Copper Split Bolt, Cu: 10-8 AWG (Str) (Run & Tap)



Features

- UL467 Listed for Direct Burial applications in earth or concrete
- Compact, high-strength, copper alloy with free-running threads and easy to grip wrench flats
- Highly resistant to cracking and corrosion

Application

For Direct Burial Applications In Earth Or Concrete, Copper

Specifications

Buy American Compliant	Yes
Certification - cULus	No
EU RoHS Indicator	Yes
Certification - UL Recognized	No
Industry Standard(s)	UL486;UL467;CSA C22.2 No 41
Buy America(n) Qualified	Buy America Compliant (All status valid till December 2025);Buy American Act Compliant (All status valid till December 2025);BABA Compliant (All status valid till December 2025)
Certification - ETL	No
Standards - Industry Standards Met	UL486;UL467;CSA C22.2 No 41
Standards - RoHS Compliance Status	CM
Certification - CSA Approved	No
UL Listed	Yes
Certification - UL Listed Direct Burial	Yes

Conductor

Conductor - Copper Solid Run	8 AWG
Conductor - Copper Solid Run Range	10 AWG-8 AWG
Conductor - Copper Solid Tap	8 AWG
Conductor - Copper Solid Tap Range	14 AWG-8 AWG
Conductor - Copper Str Run	10 AWG;9 AWG;8 AWG
Conductor - Copper Str Run Range	10 STR - 8 STR
Conductor - Copper Str Tap	14 AWG;12 AWG;10 AWG;9 AWG;8 AWG

Conductor - Copper Str Tap Range	10 STR - 8 STR
Conductor Type	CU C Solid-Run;CU C Str-Run;CU Weld C Solid-Run;CU Weld C Str-Run;CU C Str-Tap;CU Weld C Solid-Tap;CU Weld C Str-Tap;CU C Solid-Tap
Conductor - CopperWeld Solid Tap	#8
Conductor - CopperWeld Solid Tap Range	#8
Conductor - CopperWeld Str Run	#8
Conductor - CopperWeld Str Run Range	#8

Configuration

Connector Type	Split Bolt
----------------	------------

Dimensions

Dimension - L Length Overall mm	22 mm
Width	0.38 in
Dimension - Width fraction	19/50 in
Dimension - Width inch	0.38 in
Dimension - Width mm	10 mm
Dimension - B Length fraction	9/20 in
Dimension - B Length inch	.45 in
Dimension - Length Overall inch	0.85
Dimension - Cross Flats inch	0.50 in

Force Related

Installation Torque Recommended in-lb	80 in-lbs
---------------------------------------	-----------

General

Trade Name	SERVIT®
Sub Brand	SERVIT
Plated	N
Type	KS, Compact
UPC 12 Digit	781810011256
UPC 14 Digit GTIN	00781810011256
Material	Copper
Plating Type	Unplated

UPC

781810011256

Pallet Quantity

99000

Logistics

Minimum Pack Quantity 1

Carton Quantity 100

Product Assets

[Catalog \[English\]](#)



A Hubbell brand

© 2025 Hubbell Incorporated. All rights reserved
BRDY-KS15-SPEC-EN | REV 11/2025