

## KS17, Split Bolt Connector, Run/Tap: #8 AWG Str-#6 AWG Sol

By Burndy  
Catalog # [KS17](#)

Copper Split Bolt, Cu: 8 AWG (Str)-6 AWG (Sol) (Run & Tap),  
Length:1.14



### Features

- UL467 Listed for Direct Burial applications in earth or concrete
- Compact, high-strength, copper alloy with free-running threads and easy to grip wrench flats
- Highly resistant to cracking and corrosion

### Application

For Direct Burial Applications In Earth Or Concrete, Copper

### Specifications

Buy American Compliant	Yes
Certification - cULus	No
EU RoHS Indicator	Yes
Certification - UL Recognized	No
Industry Standard(s)	RUS
Buy America(n) Qualified	Buy America Compliant (All status valid till December 2025);Buy American Act Compliant (All status valid till December 2025);BABA Compliant (All status valid till December 2025)
Certification - ETL	No
Standards - Industry Standards Met	RUS
Standards - RoHS Compliance Status	CM
Certification - CSA Approved	No
UL Listed	Yes
Certification - UL Listed Direct Burial	Yes

### Conductor

Conductor - Copper Solid Run	6 AWG
Conductor - Copper Solid Run Range	8 AWG-6 AWG
Conductor - Copper Solid Tap	6 AWG
Conductor - Copper Solid Tap Range	14 AWG-6 AWG
Conductor - Copper Str Run	8 AWG;7 AWG;6 AWG
Conductor - Copper Str Run Range	8 STR - 6 STR
Conductor - Copper Str Tap	14 AWG;12 AWG;10 AWG;9 AWG;8 AWG;7 AWG;6 AWG

Conductor - Copper Str Tap Range	8 STR - 6 STR
Conductor Type	CU C Solid-Run;CU C Str-Run;CU Weld C Solid-Run;CU Weld C Str-Run;CU C Str-Tap;CU Weld C Solid-Tap;CU Weld C Str-Tap;CU C Solid-Tap
Conductor - CopperWeld Solid Run	6 AWG
Conductor - CopperWeld Solid Run Range	6 AWG
Conductor - CopperWeld Solid Tap	6 AWG
Conductor - CopperWeld Solid Tap Range	6 AWG
Conductor - CopperWeld Str Run	9-1/2D ;8A ;3#12
Conductor - CopperWeld Str Run Range	9-1/2D -3#12
Conductor - CopperWeld Str Size	9-1/2 D;8A ;3#12
Conductor - CopperWeld Str Size Range	9-1/2 D-3#12
Conductor - CopperWeld Str Tap	9-1/2 D;8A ;3#12
Conductor - CopperWeld Str Tap Range	9-1/2 D-3#12

### Configuration

Connector Type	Split Bolt
----------------	------------

### Dimensions

Dimension - L Length Overall mm	29 mm
Width	0.45 in
Dimension - Width fraction	9/20 in
Dimension - Width inch	0.45 in
Dimension - Width mm	11 mm
Dimension - B Length fraction	29/50 in
Dimension - B Length inch	.58 in
Dimension - Length Overall inch	1.14
Dimension - Cross Flats inch	0.63 in

### Force Related

Installation Torque 165 in  
Recommended in-lb

Carton Quantity 100  
Pallet Quantity 99000

### General

Trade Name SERVIT®  
Sub Brand SERVIT  
Plated N  
Type KS, Compact  
UPC 12 Digit 781810011508  
UPC 14 Digit GTIN 00781810011508  
Material Copper  
Plating Type Unplated  
UPC 781810011508

### Operational

Operating Temperature Range 0 - 90  
Celcius  
Operating Temperature Celcius 90 °C  
Max  
Operating Temperature Celcius 0 °C  
Min  
Operating Temperature Range 32 - 194  
Fahrenheit

### Logistics

Minimum Pack Quantity 100

### Product Assets

[Catalog \[English\]](#)



A Hubbell brand