


## KS223, Split Bolt Connector, Run/Tap: #6 AWG Str-#2 AWG Sol

By Burndy  
Catalog # [KS223](#)

Copper Split Bolt, Cu: 6 AWG (Str)-2 AWG (Sol) (Run & Tap)



### Features

- Compact, high-strength, copper alloy with free-running threads and easy to grip wrench flats
- Highly resistant to cracking and corrosion

### Application

For Direct Burial Applications, Copper, Copperweld

### Specifications

Buy American Compliant	No
Certification - cULus	No
EU RoHS Indicator	Yes
Certification - UL Recognized	No
Industry Standard(s)	RUS
Certification - ETL	No
Standards - Industry Standards Met	RUS
Standards - RoHS Compliance Status	CM
Certification - CSA Approved	No
UL Listed	No

### Conductor

Conductor - Copper Solid Run	2 AWG
Conductor - Copper Solid Run Range	2 AWG
Conductor - Copper Solid Tap	2 AWG
Conductor - Copper Str Run	6 AWG;5 AWG;4 AWG;3 AWG;2 AWG
Conductor - Copper Str Run Range	6 STR - 3 STR
Conductor - Copper Str Tap	14 AWG;12 AWG;10 AWG;9 AWG;8 AWG;7 AWG;6 AWG;5 AWG;4 AWG;3 AWG;2 AWG
Conductor - Copper Str Tap Range	6 STR - 3 STR
Conductor Type	CU C Solid-Run;CU C Str-Run;CU Weld C Solid-Run;CU Weld C Str-Run;CU C Str-Tap;CU Weld C Solid-Tap;CU Weld C Str-Tap
Conductor - CopperWeld Solid Run	8 AWG;7 AWG;6 AWG;5 AWG;4 AWG
Conductor - CopperWeld Solid Run Range	8 AWG-4 AWG

Conductor - CopperWeld Solid Tap	8 AWG;7 AWG;6 AWG;5 AWG;4 AWG
Conductor - CopperWeld Solid Tap Range	8 AWG-4 AWG
Conductor - CopperWeld Str Run	6 D AWG;5 A AWG;5 D AWG;5 P AWG;4 A AWG
Conductor - CopperWeld Str Run Range	6 D AWG-4 A AWG
Conductor - CopperWeld Str Tap	6 D AWG;5 A AWG;5 D AWG;5 P AWG;4 A AWG
Conductor - CopperWeld Str Tap Range	6 D AWG-4 A AWG

### Configuration

Connector Type	Split Bolt
----------------	------------

### Dimensions

Dimension - L Length Overall mm	34 mm
Width	0.6 in
Dimension - Width inch	0.84 in
Dimension - Width mm	21 mm
Dimension - Length Overall inch	1.5
Dimension - Cross Flats inch	.74 in

### Force Related

Installation Torque Recommended in-lb	275 LBS/in
---------------------------------------	------------

### General

Trade Name	SERVIT®
Sub Brand	SERVIT
Plated	N
Type	KS-3, Compact
UPC 12 Digit	781810022504
UPC 14 Digit GTIN	00781810022504
Material	Copper
Plating Type	Unplated
UPC	781810022504

### Logistics

Minimum Pack Quantity	1
Carton Quantity	100
Pallet Quantity	17400

## Product Assets

[Catalog \[English\]](#)

---



A Hubbell brand

© 2025 Hubbell Incorporated. All rights reserved  
BRDY-KS223-SPEC-EN | REV 11/2025