



KS23, Split Bolt Connector, Run/Tap: #6 AWG-#2 AWG Str

By Burndy
Catalog # [KS23](#)

Copper Split Bolt, Cu: 6 AWG-2 AWG (Str) (Run & Tap)



Features

- UL467 Listed for Direct Burial applications in earth or concrete
- Compact, high-strength, copper alloy with free-running threads and easy to grip wrench flats
- Highly resistant to cracking and corrosion

Application

For Direct Burial Applications In Earth Or Concrete, Copper

Specifications

Buy American Compliant	Yes
Certification - cULus	No
EU RoHS Indicator	Yes
Certification - UL Recognized	No
Industry Standard(s)	RUS
Buy America(n) Qualified	Buy America Compliant (All status valid till December 2025);Buy American Act Compliant (All status valid till December 2025);BABA Compliant (All status valid till December 2025)
Certification - ETL	No
Standards - Industry Standards Met	RUS
Standards - RoHS Compliance Status	CM
Certification - CSA Approved	No
UL Listed	Yes
Certification - UL Listed Direct Burial	Yes

Conductor

Conductor - Copper Solid Run	1 AWG
Conductor - Copper Solid Run Range	6 AWG-1 AWG
Conductor - Copper Solid Tap	1 AWG
Conductor - Copper Solid Tap Range	14 AWG-1 AWG
Conductor - Copper Str Run	6 AWG;5 AWG;4 AWG;3 AWG;2 AWG;1 AWG
Conductor - Copper Str Run Range	6 STR - 2 STR

Conductor - Copper Str Tap	14 AWG;12 AWG;10 AWG;8 AWG;6 AWG;4 AWG;3 AWG;2 AWG;1 AWG
Conductor - Copper Str Tap Range	6 STR - 2 STR
Conductor Type	CU C Solid-Run;CU C Str-Run;CU Weld C Solid-Run;CU Weld C Str-Run;CU C Str-Tap;CU Weld C Solid-Tap;CU Weld C Str-Tap;CU C Solid-Tap
Conductor - CopperWeld Solid Run	#1
Conductor - CopperWeld Solid Run Range	#1
Conductor - CopperWeld Solid Tap	#1
Conductor - CopperWeld Solid Tap Range	#1
Conductor - CopperWeld Str Run	3 #7;3A;5D
Conductor - CopperWeld Str Run Range	3 #7-5D
Conductor - CopperWeld Str Tap	3 #7;3A;5D
Conductor - CopperWeld Str Tap Range	3 #7-5D

Configuration

Connector Type	Split Bolt
----------------	------------

Dimensions

Dimension - L Length Overall mm	39 mm
Width	0.62 in
Dimension - Width fraction	31/50 in
Dimension - Width inch	0.62 in
Dimension - Width mm	16 mm
Dimension - B Length fraction	18/25 in
Dimension - B Length inch	.72 in
Dimension - Length Overall inch	1.54
Dimension - Cross Flats inch	0.82 in

Force Related

Installation Torque Recommended in-lb	275 in
---------------------------------------	--------

General

Trade Name SERVIT®
Sub Brand SERVIT
Plated N
Type KS, Compact
UPC 12 Digit 781810012758
UPC 14 Digit GTIN 00781810012758
Material Copper
Plating Type Unplated

UPC

781810012758

Logistics

Minimum Pack Quantity 100
Carton Quantity 100
Pallet Quantity 44000

Product Assets[Catalog \[English\]](#)**A Hubbell brand**

© 2025 Hubbell Incorporated. All rights reserved
BRDY-KS23-SPEC-EN | REV 11/2025