



KS26, Split Bolt Connector, Run/Tap: #2 AWG-2/0 AWG Str

By Burndy
Catalog # [KS26](#)



Copper Split Bolt, Cu: 2 AWG-2/0 AWG (Str) (Run & Tap)

Features

- UL467 Listed for Direct Burial applications in earth or concrete
- Compact, high-strength, copper alloy with free-running threads and easy to grip wrench flats
- Highly resistant to cracking and corrosion

Application

For Direct Burial Applications In Earth Or Concrete, Copper

Specifications

Buy American Compliant	Yes
Certification - cULus	No
EU RoHS Indicator	Yes
Certification - UL Recognized	No
Industry Standard(s)	UL 486A;UL486B
Buy America(n) Qualified	Buy America Compliant (All status valid till December 2025);Buy American Act Compliant (All status valid till December 2025);BABA Compliant (All status valid till December 2025)
Certification - ETL	No
Standards - Industry Standards Met	UL 486A;UL486B
Standards - RoHS Compliance Status	CM
Certification - CSA Approved	No
UL Listed	Yes
Certification - UL Listed Direct Burial	Yes

Conductor

Conductor - Rebar Size	3
Conductor - Rebar Size Range	3
Conductor - Copper Solid Run	3/0 AWG
Conductor - Copper Solid Run Range	2 AWG-2/0 AWG
Conductor - Copper Solid Tap	3/0 AWG
Conductor - Copper Solid Tap Range	14 AWG-2/0 AWG
Conductor - Copper Str Run	2 AWG;1 AWG;1/0 ;2/0 AWG
Conductor - Copper Str Run Range	2 STR - 2/0 STR

Conductor - Copper Str Tap	14 AWG;12 AWG;10 AWG;9 AWG;8 AWG;7 AWG;6 AWG;5 AWG;4 AWG;3 AWG;2 AWG;1 AWG;1/0 ;2/0 AWG
Conductor - Copper Str Tap Range	2 STR - 2/0 STR
Conductor Type	CU C Solid-Run;CU C Str-Run;CU Weld C Solid-Run;CU Weld C Str-Run;CU C Str-Tap;CU Weld C Solid-Tap;CU Weld C Str-Tap;CU C Solid-Tap
Conductor - CopperWeld Solid Run	3/0
Conductor - CopperWeld Solid Run Range	3/0
Conductor - CopperWeld Solid Tap	3/0
Conductor - CopperWeld Solid Tap Range	3/0
Conductor - CopperWeld Str Run	7 #7
Conductor - CopperWeld Str Run Range	7 #7
Conductor - CopperWeld Str Tap	7 #7
Conductor - CopperWeld Str Tap Range	7 #7

Configuration

Connector Type	Split Bolt
----------------	------------

Dimensions

Dimension - L Length Overall mm	49 mm
Width	0.82 in
Dimension - Width fraction	41/50 in
Dimension - Width inch	0.82 in
Dimension - Width mm	21 mm
Dimension - B Length fraction	9/10 in
Dimension - B Length inch	.90 in
Dimension - Length Overall inch	1.94
Dimension - Cross Flats inch	1.05 in

Force Related

Installation Torque
Recommended in-lb

385 in

Plating Type
UPC

Unplated
781810013281

General

Trade Name SERVIT®
Sub Brand SERVIT
Plated N
Type KS, Compact
UPC 12 Digit 781810013281
UPC 14 Digit GTIN 00781810013281
Material Copper

Logistics

Minimum Pack Quantity 1
Carton Quantity 25
Pallet Quantity 8700

Product Assets

[Catalog \[English\]](#)



A Hubbell brand

© 2025 Hubbell Incorporated. All rights reserved
BRDY-KS26-SPEC-EN | REV 11/2025