

KSA350, Aluminum Split Bolt Connector, Tin Plated

By Burndy
Catalog # [KSA350](#)

Aluminum Split Bolt, (Run, Tap):: Al-Al: 350 kcmil, 350 kcmil, Al-Cu: 1/0 AWG (Str), 4 AWG (Str), Cu-Cu: 350 kcmil, 4 AWG (Str), Tin Plated



Features

- No scratch brushing or oxide inhibitor required
- Provides maximum pressure assuring a secure connection of run and tap conductors
- UL486B Listed
- Low contact resistance, provides equal coefficient of expansion
- Inhibits the reformation of oxides by producing a gas-tight seal

Application

For All Combinations of Aluminum to Aluminum, Aluminum to Copper and Copper to Copper, Aluminum Alloy Tin Plated

Specifications

Buy American Compliant	No
Certification - cULus	No
EU RoHS Indicator	Yes
Certification - UL Recognized	No
Industry Standard(s)	UL 486A-486B
Certification - ETL	No
Standards - Industry Standards Met	UL 486A-486B
Standards - RoHS Compliance Status	CM
Certification - CSA Approved	Yes
UL Listed	Yes
Certification - UL Listed Direct Burial	No

Conductor

Conductor - AL Str Run	1/0 AWG;2/0 AWG;3/0 AWG;4/0 AWG;250 kcmil;266 kcmil;300 kcmil;336 kcmil;350 kcmil
Conductor - AL Str Run Range	1/0 AWG-350 kcmil
Conductor - AL Str Tap	4 AWG;3 AWG;2 AWG;1 AWG;1/0 AWG;2/0 AWG;3/0 AWG;4/0 AWG;250 kcmil;266 kcmil;300 kcmil;336 kcmil;350 kcmil
Conductor - AL Str Tap Range	4 AWG-350 kcmil
Conductor - Copper Solid Tap	8 AWG;7 AWG;6 AWG;5 AWG;4 AWG;3 AWG;2 AWG

Conductor - Copper Solid Tap Range	8 AWG-2 AWG
Conductor - Copper Str Run	1/0 ;2/0 AWG;3/0 AWG;4/0 AWG;250 kcmil;300 kcmil;350 kcmil
Conductor - Copper Str Run Range	1/0 -350 kcmil
Conductor Size	4 AWG-350 KCMIL
Conductor - Copper Str Tap	4 AWG;3 AWG;2 AWG;1 AWG;1/0 ;2/0 AWG;3/0 AWG;4/0 AWG;250 kcmil;300 kcmil;350 kcmil
Conductor - Copper Str Tap Range	4 AWG-350 kcmil
Conductor Type	AL C Str-Run;CU C Str-Run;CU C Solid-Run;AL C Str-Tap;CU C Str-Tap;CU C Solid-Tap

Configuration

Connector Type	Split Bolt
----------------	------------

Current

Rating - Minimum Voltage	600
--------------------------	-----

Dimensions

Dimension - L Length Overall mm	82 mm
Dimension - Height fraction	1-1/2 in
Dimension - Height inch	1.50 in
Dimension - Height mm	38.1 mm
Dimension - Width inch	1.50 in
Dimension - Width mm	38 mm
Dimension - B Length fraction	2-1/6 in
Dimension - B Length inch	2.18 in
Dimension - Bolt Size inch	1.38 in
Dimension - Length Overall inch	3.24 in
Dimension - Cross Flats inch	1.69 in

Force Related

Installation Torque Recommended in-lb	650 LBS/in
---------------------------------------	------------

General

Trade Name	TRITAP™ SERVIT®
Sub Brand	TRITAP, SERVIT
Plated	Y
Type	KSA
UPC 12 Digit	781810183526
UPC 14 Digit GTIN	00781810183526
Hardware Type	1 3/8-12 UNF
Material	Aluminum
Plating Type	Tin
UPC	781810183526

Logistics

Minimum Pack Quantity	1
Carton Quantity	20
Pallet Quantity	2880

Operational

Temperature Rating	194
--------------------	-----

Product Assets

[Catalog \[English\]](#)



A Hubbell brand

© 2025 Hubbell Incorporated. All rights reserved
BRDY-KSA350-SPEC-EN | REV 11/2025