

KSU23, Split Bolt Connector with Spacer, Tin Plated

By Burndy
Catalog # [KSU23](#)

Tin-plated, high strength copper alloy SERVIT™ with spacer. Spacer separates dissimilar conductors and provides long contact length that prevents high pressure point contacts between run and tap conductors, 1.48 IN L.

Features

- Tin-plated, high strength copper alloy with spacer
- Spacer separates dissimilar conductors and provides long contact length preventing high pressure point contacts between run and tap conductors

Application

For All Combinations Of Copper, Aluminum, ACSR, AAAC, 5005, And Steel

Specifications

Buy American Compliant	Yes
EU RoHS Indicator	Yes
Standards - RoHS Compliance Status	CM
Certification - CSA Approved	No
UL Listed	Yes
Buy America(n) Qualified	Buy America Compliant (All status valid till December 2025);Buy American Act Compliant (All status valid till December 2025);BABA Compliant (All status valid till December 2025)

Conductor

Conductor - Copper Str Run Range	8 AWG - 2 AWG
----------------------------------	---------------



Conductor - Copper Str Tap Range	8 AWG - 2 AWG
Conductor - ACSR Str Run Range	3 AWG - 2 AWG
Conductor - ACSR Str Tap Range	6 AWG - 2 AWG
Conductor - AL Str Run Range	8 AWG - 2 AWG
Conductor - AL Str Tap Range	8 AWG - 2 AWG

Dimensions

Dimension - Length Overall inch	1.56
Width	0.59 in

General

Sub Brand	UNIVERSAL SERVIT
Trade Name	SERVIT®
Plated	Y
Type	KSU, Universal
Material	Copper
Plating Type	Tin Plated
UPC	781810036006

Logistics

Minimum Pack Quantity	1
Carton Quantity	100
Pallet Quantity	17400

Product Assets

[Catalog \[English\]](#)