



KVS40

by Burndy
Catalog ID: KVS40

Prop65

Compact, two-piece, high strength, high copper alloy BURNDY OKLIP recommended for heavy duty connections. Neoprene rings hold DURIUM bolts in place during installation.Installed with ordinary wrench.Recommended tightening torque:500 in-lb.

Features: Compact, Two-Piece, High Strength, High Copper Alloy
BURNDY OKLIP Recommended For Heavy Duty Connections, Neoprene Rings Hold DURIUM Bolts In Place During Installation, Installed With Ordinary Wrench, Installation Torque: 500 IN-LB, Conductor Type: Run: Copperweld, Commercial Stranded Copper, Tap: Copperweld, Commercial Stranded Copper, Conductor Spacer: No

Product Details

General

Application	For Copper And Copperweld, Heavy Duty Connections
Installation Torque Recommended in-lb	500 LBS/in
Item Type	3B
Material	Copper
Plated	N
Plating Type	Unplated
Sub Brand	OKLIP
Trade Name	OKLIP™
Type	KVS
UPC	781810063903
UPC 12 Digit	7818100639033

Dimensions

Dimension - Height inch	3.19 in
Dimension - Stud Size inch	1/2 in
Dimension - Width inch	2.50 in

Conductor Related

Conductor - Copper Str Run Range	400 - 800 kcmil
Conductor - Copper Str Tap Range	3/0 str. - 800 kcmil
Conductor Type	• CU C Str-Run • CU C Str-Tap • CU Weld C Solid-Run • CU Weld C Solid-Tap

Certifications and Compliance

Certification - CSA Approved	No
Certification - ETL	No
Certification - UL Recognized	No

Certification - cULus	No
Industry Standard(s)	UL486C
Standards - Industry Standards Met	UL486C
Standards - RoHS Compliance Status	CM
UL Listed	Yes

Logistics

Minimum Pack Quantity	1
-----------------------	---

For further technical assistance, please contact us

BURNDY Headquarters
47 East Industrial Park Drive
Manchester, New Hampshire 03109

Customer Service Hours:
8 AM - 8 PM Eastern Monday-Friday
Emergency Service 24-hours/365 Days
Phone: 1-800-346-4175
1-603-647-5299 (International)