

KVSU28, Mechanical Connector with Spacer Bar

By Burndy
Catalog # [KVSU28](#)



Tin plated copper alloy with tin plated hardware; spacer bar to separate dissimilar conductors

Features

- Compact, tin-plated high strength copper alloy connector with spacer and tin-plated silicon bronze hardware
- Recommended for heavy duty connections
- Spacer separates dissimilar conductors and provides long contact length
- Neoprene ring prevents loss of shorter bolt during installation
- Longer peened bolt permits swivel action for easier installation

Application

For All Combinations Of Copper, Aluminum, ACSR, AAAC And 5005

Specifications

Buy American Compliant	No
Certification - cULus	No
EU RoHS Indicator	Yes
Certification - UL Recognized	No
Certification - ETL	No
Standards - RoHS Compliance Status	EX
Certification - CSA Approved	No
UL Listed	No

Conductor

Conductor - Galvanized Steel Str Run Range	3/8 in- 1/2 in
Conductor - Galvanized Steel Str Tap Range	5/32 in- 1/2 in
Conductor - ACSR Str Run Range	1/0 ACSR - 4/0 ACSR
Conductor - ACSR Str Tap Range	6 ACSR - 4/0 ACSR
Conductor - AL Str Run Range	1/0 str. - 4/0 str.
Conductor - AL Str Tap Range	6 str.- 4/0 str.
Conductor - Copper Solid Run Range	2/0 AWG;3/0 AWG;4/0 AWG
Conductor - Copper Solid Run Range	2/0 AWG-4/0 AWG
Conductor - Copper Solid Tap Range	2/0 AWG;3/0 AWG;4/0 AWG
Conductor - Copper Solid Tap Range	2/0 AWG-4/0 AWG
Conductor - Copper Str Run Range	1/0 str. - 4/0 str.

Conductor - Copper Str Tap Range	6 str.- 4/0 str.
Conductor Type	AL C Str-Run;AL C Str-Tap;CU C Str-Run;CU C Str-Tap;AAAC C 5005-Run;AAAC C 5005-Tap;AAAC C 6201-Run;AAAC C 6201-Tap;ACSR C Str-Run;ACSR C Str-Tap;CU C Solid-Run;CU C Solid-Tap;GAL Steel C Str-Run;GAL Steel C Str-Tap;Cu Weld Sol.- Run;Cu Weld Sol.- Tap
Conductor - CopperWeld Solid Run Range	2/0 sol.- 4/0 sol.
Conductor - CopperWeld Solid Tap Range	6 sol.- 4/0 sol.

Dimensions

Dimension - L Length Overall mm	29 mm
Dimension - Height fraction	2-3/8 in
Dimension - Height inch	2.50 in
Dimension - Height mm	63.50 mm
Dimension - Stud Size inch	3/8 in
Dimension - Width fraction	1-3/4 in
Dimension - Width inch	1.67 in
Dimension - Width mm	44 mm
Dimension - Length Overall inch	1.04 in

Force Related

Installation Torque Recommended in-lb	250 LBS/in
---------------------------------------	------------

General

Trade Name	OKLIP™
Sub Brand	OKLIP
Plated	Y
Construction Material - Main Type	Copper alloy
UPC 12 Digit	KVS, Compact, Universal 781810081808
UPC 14 Digit GTIN	00781810081808
Material	Copper
Plating Type	Tin
Finish Type	Tin-Plated
UPC	781810081808

Logistics

Minimum Pack Quantity 1
Carton Quantity 25

Pallet Quantity 3000

Product Assets

[Catalog \[English\]](#)



A Hubbell brand

© 2025 Hubbell Incorporated. All rights reserved
BRDY-KVSU28-SPEC-EN | REV 11/2025