



# HYTOOL™ Series, Hand-Operated Crimper, Installs #14 - 4/0 AWG, Permanent BG (5/8) and D3 grooves

By Burndy  
Catalog # MD6

HYTOOL™ #14-4/0, Permanent BG/D3

## Features

- Ergonomically designed, one-piece, composite polymer handles
- Comfort grip handles
- Time-proven steel jaw designs
- No tool adjustment required
- 99,000 crimp/cycle life
- Positive lock, spring loaded die retainer buttons
- PTFE impregnated steel/bronze bushings and stainless steel pins
- Electroless nickel plated jaws and jaw links

## Application

Crimping

## Specifications

Buy American Compliant	No
EU RoHS Indicator	Yes
Standards - RoHS Compliance Status	EX

## Conductor

Crimping Ranges	<ul style="list-style-type: none"> <li>• Copper: 10 sol. - 500 Kcmil</li> <li>• Copper Flex: #8 to 350 kcmil</li> </ul>
-----------------	---

## Dimensions

Length	25.38 in
--------	----------



Width	7.04 in
Weight	6.25 lb.
Height	2 in
Dimensions	25.38 in x 7.04 in x 2 in

## Force Related

Crimp Force Capacity	4.5 ton
----------------------	---------

## General

Sub Brand	HYTOOL
Series	HYTOOL™ Series
Trade Name	HYTOOL™
Application - For Use On	Copper, Aluminum, ACSR, Steel, Copperweld, Alumoweld, 6201, 5005, Compressed and Compact Conductors
UPC 12 Digit	781810446003
UPC 14 Digit GTIN	00781810446003
Tool Type	Hand Operated Crimper
UPC	781810446003
Die Type	W Die and X Die

## Logistics

Package Contents	Tool only
Minimum Pack Quantity	1

## Product Assets

- [Catalog \[English\]](#)
- [Installation Manual \[English\]](#)