



HYTOOL™ Hand-Operated Crimper, Installs #14 - 4/0 AWG, Permanent O and D3 grooves

By Burndy
Catalog # [MD68](#)



Crimper, Installs #14-4/0 AWG, O & D3 Grooves.

Features

- Ergonomically designed, one-piece, composite polymer handles
- Comfort grip handles
- Time-proven steel jaw designs
- No tool adjustment required
- 99,000 crimp/cycle life
- Positive lock, spring loaded die retainer buttons
- PTFE impregnated steel/bronze bushings and stainless steel pins
- Electroless nickel plated jaws and jaw links

Application

- Crimping

General

Application - For Use On	Copper, Aluminum, ACSR, Steel, Copperweld, Alumoweld, 6201, 5005, Compressed and Compact Conductors
Catalog Number	MD68
Crimp Force Capacity	4.5 ton
Die Type	W Die and X Die
EU RoHS Indicator	Yes
Sub Brand	HYTOOL
Tool Type	Hand Operated Crimper
Trade Name	HYTOOL™
UPC	781810446553
UPC 12 Digit	7818104465533

Dimensions

Dimensions	25.38 in x 7.04 in x 2.00 in
Height	2 in
Length	25.38 in
Weight	6 lb
Width	7.04 in

Conductor Related

Crimping Ranges	Copper: 10 sol. - 500 Kcmil; Copper Flex: #8 to 350 kcmil
-----------------	--

Certifications And Compliance

Standards - RoHS Compliance	EX
Status	

Logistics

Minimum Pack Quantity	1
Package Contents	Tool only

Product Assets

Catalogs - Full Line BURNDY Catalog
Catalogs - Section N - Tooling
Customer Notices - Prop 65 Notice
Product Cross Section Image(s) - BUR_MD68_LA
Sales Drawings - SE068728



A proud member of the Hubbell Family.

©2024 Hubbell Incorporated. All rights reserved.
BRDY-MD68-SPEC-EN | REV 6/2024