



NAH292N, 2-Hole Substation Cu Cable to Pad, #6 Sol-250 kcmil

By Burndy
Catalog # [NAH292N](#)

Cast Copper alloy terminal, 6 Sol-250 kcmil , 5.88 in Length,
Cable to Pad.



Features

- High copper alloy reversible cap terminal for joining a wide range of cable to equipment pads
- Tongue is side-formed to provide adequate clearance and terminal is designed for 1-wrench installation

Application

Substation

General

Catalog Number	NAH292N
Clamping Element Design	Body and Cap
EU RoHS Indicator	Yes
Material	Copper Alloy
Material - Hardware	DURIUM™ Silicon Bronze
One Wrench Installation	Y
Physical Attribute - Number of Holes	2
Physical Attribute - Pad Alignment	Offset
Physical Attribute - Pad Configuration	1.50 x 3 - 2 holes
Physical Attribute - Pad Orientation	Straight
Sub Brand	SUBSTATION CONNECTOR
Type	NAH
UPC	781810002278
UPC 14 Digit GTIN	00781810002278

Dimensions

Dimension - B Length fraction	2-31/50 in
Dimension - D inch	3.00 in
Dimension - F Width Center to Center inch	1.75 in
Dimension - Height fraction	2-3/25 in
Dimension - Height inch	2.12 in
Dimension - Height mm	53.8 mm
Dimension - Hole Size fraction	9/16
Dimension - Hole Size inch	0.56 in
Dimension - N inch	0.62 in
Dimension - Pad Size inch	1.5 x 3
Dimension - Pad Width inch	1.50 in

Dimension - Width fraction	2-11/25 in
Dimension - Width inch	2.44 in
Dimension - Width mm	62 mm

Conductor Related

Conductor - Connection Combination	Cable to Flat
Conductor - Copper Solid Size	6 AWG;5 AWG;4 AWG;3 AWG;2 AWG;1 AWG;1/0 AWG;2/0 AWG;3/0 AWG;4/0 AWG
Conductor - Copper Solid Size Range	6 AWG-4/0 AWG
Conductor - Copper Str Size Range	6 AWG-250 kcmil
Conductor Type	<ul style="list-style-type: none">• CU C Str-Size• CU C Solid-Size
Number of Conductors	1

Certifications And Compliance

Buy America(n) Qualified	TAA Compliant (All status valid till December 2025)
Standards - RoHS Compliance Status	EX
UL Listed	No

Logistics

Carton Quantity	6
Minimum Pack Quantity	1

Product Assets

[3D Models - NAH292N_MODEL-IGES](#)
[3D Models - NAH292N_MODEL-PDF](#)
[3D Models - NAH292N_MODEL-STEP](#)
[Catalogs - BURNDY Master Catalog - Full Line BURNDY Catalog](#)
[Catalogs - BURNDY Master Catalog - Section L - Bolted Substation](#)
[Customer Notices - Prop 65 Notice](#)
[Interactive Catalog - BURNDY Full-Line Digital Catalog](#)
[Product Cross Section Image\(s\) - BUR_NAH292N_LineArt](#)
[Sales Drawings - SE079584-01](#)
[Specifications - NAH292N](#)



A Hubbell brand

©2025 Hubbell Incorporated. All rights reserved
BRDY-NAH292N-SPEC-EN | REV 7/2025