


By Burndy
 Catalog # [PENA1/2](#)

Oxide Inhibiting Electrical Joint Compound, 1/2 OZ, For Al-Al, Al-Cu & Al Conduit Threads



Features

- PENETROX™ Oxide Inhibiting Joint Compounds are available in many types
- PENETROX A is a natural compound recommended for aluminum to aluminum, aluminum to copper connections and aluminum conduit threads, it is not recommended for use with rubber or polyethylene insulated conductors
- PENETROX A13 is a synthetic base compound with evenly suspended zinc particles recommended for aluminum to aluminum, aluminum to copper, and also aluminum conduit threads
- PENETROX E is a synthetic base with evenly suspended copper particles, recommended for copper to copper, copper threads, and all grounding applications

Application

For Aluminum To Copper, Aluminum To Aluminum, Aluminum To Conduit

Specifications

Buy American Compliant	Contact Manufacturer
EU RoHS Indicator	Yes
Standards - RoHS Compliance Status	CM
UL Listed	Yes
Buy America(n) Qualified	Contact Manufacturer

General

Sub Brand	PENETROX
Trade Name	PENETROX™
Application - For Use On	Aluminum to Aluminum;Aluminum to Conduit;Aluminum to Copper
Pour Point	-15 °F
Type	A
UPC 12 Digit	781810592601
UPC 14 Digit GTIN	00781810592601
Container Type	Tube
UPC	781810592601

Logistics

Minimum Pack Quantity	50
Container Size	1/2 oz
Carton Quantity	50

Operational

Temperature - Dropping Point Fahrenheit	230 °F
Viscosity at 100 Fahrenheit	305 °F

Product Assets

[Catalog \[English\]](#)