



By Burndy
Catalog # [PENA4](#)

Oxide Inhibiting Electrical Joint Compound, 4 OZ, For Al-Al, Al-Cu & Al Conduit Threads



Features

- PENETROX™ Oxide Inhibiting Joint Compounds are available in many types
- PENETROX A is a natural compound recommended for aluminum to aluminum, aluminum to copper connections and aluminum conduit threads, it is not recommended for use with rubber or polyethylene insulated conductors
- PENETROX A13 is a synthetic base compound with evenly suspended zinc particles recommended for aluminum to aluminum, aluminum to copper, and also aluminum conduit threads
- PENETROX E is a synthetic base with evenly suspended copper particles, recommended for copper to copper, copper threads, and all grounding applications

Application

Aluminum to Aluminum, Aluminum to Conduit, Aluminum to Copper

Specifications

Buy American Compliant	No
EU RoHS Indicator	Yes
Standards - RoHS Compliance Status	CM
UL Listed	Yes

General

Sub Brand	PENETROX
Trade Name	PENETROX™
Application - For Use On	Aluminum to Aluminum;Aluminum to Conduit;Aluminum to Copper
Pour Point	-15 °F
Type	Sealing compound
UPC 12 Digit	781810593103
UPC 14 Digit GTIN	00781810593103
Container Type	Squeeze Bottle
UPC	781810593103

Logistics

Minimum Pack Quantity	1
Container Size	4 oz
Carton Quantity	12
Pallet Quantity	4032

Operational

Temperature - Dropping Point Fahrenheit	230 °F
Viscosity at 100 Fahrenheit	305 °F

Product Assets

[Catalog \[English\]](#)