



# QA342N, Heavy Duty Two Hole Mounting Copper Lug Connector, 400-500 kcmil, 1/2" Stud, 1-3/4" Spacing, 1 Screw



By Burndy  
Catalog # [QA342N](#)

Copper Terminal, Heavy Duty, 2 Hole, 400-500 kcmil, 1/2" Stud, 1-3/4" Stud Hole Spacing, 1 Screw.

## Features

- QIKLUG™ Terminals feature compact size, high copper alloy terminal for joining cables to equipment pads or bars
- Each element accommodates a wide range of cable
- One-wrench installation

## Application

For Copper Cable

## General

Catalog Number	QA342N
Connector Type	Single Clamp
EU RoHS Indicator	Yes
Installation Torque Recommended in-lb	375 LBS/in
Material	Copper
Physical Attribute - Number of Holes	2
Physical Attribute - Number of Screws	1
Physical Attribute - Screw Type	Hexagonal Bolt
Plated	N
Plating Type	Unplated
Sub Brand	QIKLUG
Temperature Rating	194
Trade Name	QIKLUG™
Type	Bolted Lugs & Terminals
UPC	781810316603
UPC 12 Digit	7818103166033

## Dimensions

Dimension - Bolt Size fraction	1/2
Dimension - D inch	3.09 in
Dimension - F Width Center to Center inch	1.75 in
Dimension - Height fraction	2
Dimension - Height inch	1.94 in
Dimension - Hole Size fraction	9/16
Dimension - Hole Size inch	0.56 in
Dimension - Hole Size mm	14 mm
Dimension - L Length Overall mm	119 mm
Dimension - Length Overall inch	4.69 in

## Electrical Ratings

Rating - Minimum Voltage 600

## Conductor Related

Conductor - Copper Str Navy Size	400 (127) Navy;500 (127) Navy
Conductor - Copper Str Navy Size Range	400 (127) Navy-500 (127) Navy
Conductor - Copper Str Size	400 kcmil;450 kcmil;500 kcmil
Conductor - Copper Str Size Range	400 kcmil-500 kcmil
Conductor Size	400-500 kcmil
Conductor Type	<ul style="list-style-type: none"><li>• CU C Str-Size</li><li>• CU C Str Navy-Size</li></ul>

## Certifications And Compliance

Certification - CSA Approved	No
Certification - ETL	No
Certification - UL Recognized	No
Certification - cULus	No
Industry Standard(s)	UL 486A-486B
Standards - Industry Standards Met	UL 486A-486B
Standards - RoHS Compliance Status	EX
UL Listed	Yes

## Logistics

Minimum Pack Quantity 1

## Product Assets

[Catalogs - Full Line BURNDY Catalog](#)  
[Catalogs - Section A - Mechanical](#)  
[Customer Notices - Prop 65 Notice](#)  
[Product Cross Section Image\(s\) - BUR\\_QA\\_LineArt](#)  
[Sales Drawings - sa008947](#)

Dimension - N inch 0.62 in  
Dimension - Pad Width inch 1.38 in  
Dimension - Stud Size inch 1/2

---



A proud member of the Hubbell Family.

©2024 Hubbell Incorporated. All rights reserved.  
BRDY-QA342N-SPEC-EN | REV 6/2024