

QGFL29B1T6, Bartap, Cable to Flat, #6 Str-250 kcmil

By Burndy
 Catalog # [QGFL29B1T6](#)

Substation Connectors



Features

- High copper alloy BARTAP™ for joining a range of cable to bar or pad
- Can be installed side by side or in-line on NEMA drilled bar
- 1-wrench installation

Application

Substation

Specifications

Buy American Compliant	No
Certification - cULus	No
EU RoHS Indicator	Yes
Certification - UL Recognized	No
Certification - ETL	No
Standards - RoHS Compliance Status	EX
Certification - CSA Approved	No
UL Listed	No
Certification - UL Listed Direct Burial	Yes

Conductor

Conductor - Copper Str Size	<ul style="list-style-type: none"> • #6 Str • 5 AWG • 4 AWG • 3 AWG • 2 AWG • 1 AWG • 1/0 • 2/0 AWG • 3/0 AWG • 4/0 AWG • 250 kcmil
Conductor - Copper Str Size Range	#6 Str-250 kcmil
Conductor Type	<ul style="list-style-type: none"> • CU C Str-Size • CU C Solid-Size

Configuration

Connector Type Bus Bar Clamp and Accessories

Dimensions

Package Length	7.06 in
Package Width	6.13 in
Package Weight	13 lb.
Dimension - Height fraction	3-1/8 in
Dimension - Height inch	3.13 in
Package Height	4.5 in
Dimension - Height mm	79.5 mm
Dimension - Width fraction	1-3/8 in
Dimension - Width inch	1.38 in
Dimension - Width mm	35 mm
Dimension - B Length fraction	1-5/8 in
Dimension - B Length inch	1.63 in

General

Material - Hardware	DURIUM™ Silicon Bronze
Trade Name	BARTAP™
Sub Brand	BARTAP
Plated	N
Type	QGFL
UPC 12 Digit	781810005910
UPC 14 Digit GTIN	00781810005910
Material	Copper Alloy
Plating Type	Unplated
UPC	781810005910

Logistics

Minimum Pack Quantity	1
Carton Quantity	25
Pallet Quantity	2700

Product Assets

[Catalog \[English\]](#)