

# QP14F25X03BG25, Vinyl Female Quick Disconnect For 16 - 14 AWG (.25 x .03)

By Burndy  
Catalog # [QP14F25X03BG25](#)



Vinyl Female Quick Disconnect For 16 - 14 AWG (.25 x .03).

## Features

- Butted seam
- Insulated connectors eliminate the need for post installation insulation
- Funnel entry barrel opening for quick and easy wire insertion
- Dimpled female socket detent ensure firm grip

## Application

For quickly connecting or disconnecting a terminal

## General

Catalog Number	QP14F25X03BG25
EU RoHS Indicator	Yes
Insulation	Y
Insulation Type	Vinyl
Material	Brass
Sub Brand	FINGRIP
Trade Name	FINGRIP™
Type	Disconnect Connectors
UPC	781810486238
UPC 14 Digit GTIN	00781810486238

## Dimensions

Dimension - B Length fraction	1/5 in
Dimension - F Width Center to Center inch	0.08 in

Dimension - Width inch 0.26 in

## Conductor Related

Conductor - Copper Str Size Range	16 AWG - 14 AWG
Conductor Type	CU C Str-Size

## Certifications And Compliance

Buy America(n) Qualified	Contact Manufacturer
Industry Standard(s)	UL467
Standards - Industry Standards	UL310
Met	
Standards - RoHS Compliance	CM
Status	
UL Listed	Yes

## Logistics

Carton Quantity	5
Minimum Pack Quantity	5

## Product Assets

[Catalogs - BURNDY Master Catalog - Full Line BURNDY Catalog](#)  
[Interactive Catalog - BURNDY Full-Line Digital Catalog](#)  
[Product Cross Section Image\(s\) - BUR\\_QP10F25X03BG25\\_LineArt](#)  
[Sales Drawings - 10104489](#)  
[Specifications - QP14F25X03BG25](#)