

## QPX2C2C, Heavy Duty Copper Tapping Connector, Run #6-#2 AWG; Tap #6-#2 AWG

By Burndy  
Catalog # [QPX2C2C](#)



VERSITAP™ Mechanical Parallel Clamp for Copper, Run & Tap: #6-#2 AWG

### Features

- VERSITAP™ Type QPX Parallel Clamps for copper are capable of Tee, Cross, Parallel, Butt and Tap configurations
- Range-taking, only 10 connectors are required to accommodate conductor sizes from #6 Stranded to 1000 kcmil
- Edges are rounded for easy taping

### Application

For Tee, Cross, Parallel, Butt And Tap Connections, Copper

### Specifications

|   |                      |
|---|----------------------|
| Buy American Compliant                  | Contact Manufacturer |
| Certification - cULus                   | No                   |
| EU RoHS Indicator                       | Yes                  |
| Certification - UL Recognized           | No                   |
| Industry Standard(s)                    | UL 486A-486B         |
| Buy America(n) Qualified                | Contact Manufacturer |
| Certification - ETL                     | No                   |
| Standards - Industry Standards Met      | UL 486A-486B         |
| Standards - RoHS Compliance Status      | EX                   |
| Certification - CSA Approved            | Yes                  |
| UL Listed                               | Yes                  |
| Certification - UL Listed Direct Burial | No                   |

### Conductor

|                                  |   |
|----------------------------------|---|
| Conductor - Nominal Diameter     | 0.179, 0.182, 0.184, 0.199, 0.206, 0.219, 0.223, 0.225, 0.230, 0.232, 0.246, 0.258, 0.260, 0.276, 0.290, 0.310, 0.320, 0.326  |
| Conductor - Copper Str Run       | <ul style="list-style-type: none"> <li>• 6 AWG</li> <li>• 5 AWG</li> <li>• 4 AWG</li> <li>• 3 AWG</li> <li>• 2 AWG</li> </ul> |
| Conductor - Copper Str Run Range | 6 AWG-2 AWG   |
| Conductor - Copper Str Tap       | <ul style="list-style-type: none"> <li>• 6 AWG</li> <li>• 5 AWG</li> <li>• 4 AWG</li> </ul>                                   |

|                                  |   |
|----------------------------------|---|
| Conductor - Copper Str Tap Range | <ul style="list-style-type: none"> <li>• 3 AWG</li> <li>• 2 AWG</li> </ul>                                      |
| Conductor Type                   | <ul style="list-style-type: none"> <li>• 6 AWG-2 AWG</li> <li>• CU C Str-Run</li> <li>• CU C Str-Tap</li> </ul> |

### Configuration

|                                       |                 |
|---------------------------------------|-----------------|
| Physical Attribute - Number of Screws | 2               |
| Connector Type                        | Universal Clamp |

### Current

|                          |     |
|--------------------------|-----|
| Rating - Minimum Voltage | 600 |
|--------------------------|-----|

### Dimensions

|                               |          |
|-------------------------------|----------|
| Dimension - L Length Overall  | 33 mm    |
| Dimension - Height fraction   | 1-1/2    |
| Dimension - Height inch       | 1.5      |
| Dimension - Height mm         | 38.1 mm  |
| Dimension - Width fraction    | 1-3/8 in |
| Dimension - Width inch        | 1.38     |
| Dimension - Width mm          | 35 mm    |
| Dimension - B Length fraction | 1/3 in   |
| Dimension - B Length inch     | 0.31 in  |
| Dimension - Length Overall    | 1.31 in  |

### Force Related

|                                       |            |
|---------------------------------------|------------|
| Installation Torque Recommended in-lb | 180 LBS/in |
|---------------------------------------|------------|

### General

|                                 |                        |
|---------------------------------|------------------------|
| Material - Hardware Trade Name  | DURIUM™ Silicon Bronze |
| Sub Brand                       | VERSITAP™              |
| Physical Attribute - Screw Type | Hexagonal Bolt         |
| Plated                          | N                      |
| Type                            | QPX                    |
| UPC 12 Digit                    | 781810341506           |
| UPC 14 Digit GTIN               | 00781810341506         |
| Material                        | Copper                 |
| Plating Type                    | Unplated               |

UPC 781810341506

### Operational

Temperature Rating 194

### Logistics

Minimum Pack Quantity 1  
Carton Quantity 1  
Pallet Quantity 1

---

### Product Assets

[Catalog \[English\]](#)



A Hubbell brand