

QQA262, Twin Clamping Two Hole Mounting Heavy Duty Copper Lug Connector



By Burndy
Catalog # [QQA262](#)

Copper Terminal, Heavy Duty, 2 Hole, 1/0-2/0 AWG (Str), 3/8" Stud, 1" Stud Hole Spacing, 2 Screws

Features

- QIKLUG™ Terminals feature compact size, high copper alloy terminal for joining cables to equipment pads or bars
- Each element accommodates a wide range of cable
- One-wrench installation

Application

For Joining Copper Cable To Equipment Pads Or Bars

Specifications

| | |
|------------------------------------|----------------------|
| Buy American Compliant | Contact Manufacturer |
| Certification - cULus | No |
| EU RoHS Indicator | Yes |
| Certification - UL Recognized | No |
| Industry Standard(s) | UL 486A-486B |
| Buy America(n) Qualified | Contact Manufacturer |
| Certification - ETL | No |
| Standards - Industry Standards Met | UL 486A-486B |
| Standards - RoHS Compliance Status | EX |
| Certification - CSA Approved | No |
| UL Listed | Yes |

Conductor

| | |
|--|----------------------------------|
| Conductor - Copper Str Size | 1/0 ;2/0 AWG |
| Conductor - Copper Str Navy Size | 100 (61) Navy;125 (61) Navy |
| Conductor - Copper Str Navy Size Range | 100 (61) Navy-125 (61) Navy |
| Conductor Size | 1/0-2/0 AWG |
| Conductor - Copper Str Size Range | 1/0 -2/0 AWG |
| Conductor Type | CU C Str-Size;CU C Str Navy-Size |

Configuration

| | |
|---------------------------------------|---|
| Physical Attribute - Number of Holes | 2 |
| Physical Attribute - Number of Screws | 2 |

Connector Type Duel Clamp

Dimensions

| | |
|---|----------|
| Dimension - F Width Center to Center inch | 1.00 in |
| Dimension - L Length Overall mm | 106 mm |
| Dimension - Pad Width inch | 0.81 in |
| Dimension - Height fraction | 1.125 in |
| Dimension - Height inch | 1.13 in |
| Dimension - Height mm | 28.7 mm |
| Dimension - Hole Size inch | 0.41 in |
| Dimension - Hole Size mm | 10 mm |
| Dimension - Bolt Size fraction | 3/8 |
| Dimension - Length Overall inch | 4.19 in |
| Dimension - D inch | 1.94 in |
| Dimension - N inch | 0.44 in |

Force Related

| | |
|---------------------------------------|------------|
| Installation Torque Recommended in-lb | 180 LBS/in |
|---------------------------------------|------------|

General

| | |
|--|------------------------------|
| Trade Name | QIKLUG™ |
| Sub Brand | MECHANICAL CONNECTOR, QIKLUG |
| Physical Attribute - Screw Type Plated | Hexagonal Bolt N |
| Type | Bolted Lugs & Terminals |
| UPC 14 Digit GTIN | 00781810325858 |
| Material | Copper |
| Plating Type | Unplated |
| UPC | 781810325858 |

Logistics

| | |
|-----------------------|---|
| Minimum Pack Quantity | 1 |
| Carton Quantity | 1 |
| Pallet Quantity | 1 |

Product Assets

[Catalog \[English\]](#)