

SP10, Vinyl Splice For 12 - 10 AWG

By Burndy
Catalog # SP10



Vinyl Splice For 12 - 10 AWG

Features

- Manufactured from seamless electrolytic copper tubing to provide maximum conductivity and tensile strength in a high quality design with no seams to split
- Funnel entry for easy wire insertion
- Electro-tin plating provides durable, long lasting resistance to corrosion

Application

For Accommodating A Broad Range Of 600 Volt Cables

Specifications

Buy American Compliant	Contact Manufacturer
Certification - cULus	No
EU RoHS Indicator	Yes
Certification - UL Recognized	No
Certification - ETL	No
Standards - Industry Standards Met	UL486
Standards - RoHS Compliance Status	CM
Certification - CSA Approved	Yes
UL Listed	Yes

Conductor

Conductor - Copper Str Size	<ul style="list-style-type: none"> • 12 AWG • 10 AWG
Conductor Size	12 - 10 AWG
Conductor - Copper Str Size Range	12 - 10 AWG

Configuration

Connector Type	Seamless Butt Splice
----------------	----------------------

Current

Voltage - Maximum	600 V
-------------------	-------

Dimensions

Dimension - Outside Diameter inch	0.26 in
Dimension - L Length Overall mm	31 mm
Dimension - Strip Length inch	21/64 in
Cable Insulation Diameter Maximum	0.260 in
Dimension - Length Overall inch	1.23 in
Dimension - Diameter Max Size inch	0.26 in

General

Insulation Type	Vinyl
Trade Name	VINYLINK™
Insulation	Y
Sub Brand	VINYLINK
Color Code	Yellow
Plated	Y
Feature - Barrel Style Type	Shrouded SP
UPC 12 Digit	781810710012
UPC 14 Digit GTIN	00781810710012
Material	Copper
Plating Type	Tin
UPC	781810710012

Logistics

Minimum Pack Quantity	40
Carton Quantity	480
Pallet Quantity	99999

Operational

Temperature Rating	105° C
--------------------	--------

Product Assets

[Catalog \[English\]](#)