

T1410, Uninsulated Ring Terminal For 16 - 14 AWG

By Burndy
Catalog # [T1410](#)



Uninsulated Ring Terminal For 16 - 14 AWG

Features

- Constructed of pure electrolytic copper for maximum conductivity, low resistance and ductility for excellent crimp forming properties
- Long brazed seam barrel and deep V groove inner serrations provide optimal conductivity, reliability and holding power after crimping
- Wire range is clearly marked on terminal for easy identification
- Long neck terminal permits easy bending and stacking of several terminals on a common stud

Application

For Control Wiring And Other Standard Duty Applications

Specifications

Buy American Compliant	Contact Manufacturer
Certification - cULus	No
EU RoHS Indicator	Yes
Certification - UL Recognized	No
Industry Standard(s)	UL467
Buy America(n) Qualified	Contact Manufacturer
Certification - ETL	No
Standards - Industry Standards Met	UL486
Standards - RoHS Compliance Status	CM
Certification - CSA Approved	Yes
UL Listed	Yes

Conductor

Conductor - Copper Str Size	<ul style="list-style-type: none"> • 20 AWG • 18 AWG • 16 AWG • 14 AWG
Conductor - Copper Solid Size	<ul style="list-style-type: none"> • 20 • 18 AWG • 17 AWG • 16 AWG • 15 AWG • 14 AWG
Conductor - Copper Solid Size Range	20 -14 AWG
Conductor Size	16 - 14 AWG

Conductor - Copper Str Size Range	20 AWG - 14 AWG
Conductor Type	<ul style="list-style-type: none"> • CU C Str-Size • CU C Solid-Size

Configuration

Physical Attribute - Number of Holes	1
Connector Type	Ring Terminal

Dimensions

Dimension - L Length Overall mm	20 mm
Dimension - Pad Width inch	0.31 in
Dimension - Hole Size fraction	1/5
Dimension - Hole Size inch	0.20 in
Dimension - Strip Length inch	9/32
Dimension - Stud Size inch	<ul style="list-style-type: none"> • #8 • #10
Dimension - B Length fraction	13/50 in
Dimension - B Length inch	0.26 in
Dimension - Z inch	0.33 in
Dimension - Bolt Size fraction	#8 - #10
Cable Insulation Diameter Maximum	0.080 in
Dimension - Length Overall inch	0.77 in
Dimension - Diameter Max Size inch	0.08 in

General

Trade Name	HYLUG™
Sub Brand	HYLUG
Physical Attribute - Tongue Type	Ring
Plated	Y
Feature - Barrel Type	Long
Type	Ring Tongue
UPC 12 Digit	781810722442
UPC 14 Digit GTIN	00781810722442
Material	Copper
Plating Type	Tin - Electro Plated
UPC	781810722442

Logistics

Minimum Pack Quantity 100
Carton Quantity 1200
Pallet Quantity 99999

Product Assets

[Catalog \[English\]](#)



A Hubbell brand

© 2025 Hubbell Incorporated. All rights reserved
BRDY-T1410-SPEC-EN | REV 12/2025