

## TN146LF, Nylon Locking Fork Terminal For 16 - 14 AWG

By Burndy  
Catalog # [TN146LF](#)



Snap Fork Tongue Terminal, CU Conductor Range: 16-14 AWG, .81 IN L.

### Features

- Locking fork tongue design allows fast installation - screw only has to be loosened for termination
- Internal configuration of the fork prevents the terminal from coming off the screw without applying a pulling force
- Locking fork is made from a copper alloy and permits many installations while maintaining proper spring retention of forks

### Application

Power Connector

### General

Catalog Number	TN146LF
Connector Type	Locking Fork Terminal
EU RoHS Indicator	Yes
Insulation	Y
Insulation Type	Nylon
Material	Copper
Physical Attribute - Tongue Type	Fork
Plated	Y
Plating Type	Unplated
Sub Brand	HYDENT
Trade Name	INSULUG™
Type	TN
UPC	781810524190
UPC 14 Digit GTIN	00781810524190

### Dimensions

Dimension - Bolt Size fraction	#4 - #6
Dimension - L Length Overall mm	24 mm

Dimension - Length Overall inch	0.93 in
Dimension - Pad Width inch	0.25 in
Dimension - Strip Length inch	7/32
Dimension - Stud Size inch	#4;#6
Dimension - Z (inch)	0.30 in

### Conductor Related

Conductor Range	#14 AWG to #16 AWG
Conductor Size	16 - 14 AWG
Conductor Type	<ul style="list-style-type: none"><li>• CU C Solid-Size</li><li>• CU C Str-Size</li></ul>

### Certifications And Compliance

Buy America(n) Qualified	Contact Manufacturer
Certification - ETL	No
Certification - UL Recognized	No
Certification - cULus	No
Standards - RoHS Compliance	CM
Status	
UL Listed	No

### Logistics

Carton Quantity	100
Minimum Pack Quantity	100

### Product Assets

[Catalogs - BURNDY Master Catalog - Section B - Small Terminals](#)  
[Catalogs - BURNDY Master Catalog - Full Line BURNDY Catalog](#)  
[Interactive Catalog - BURNDY Full-Line Digital Catalog](#)  
[Product Cross Section Image\(s\) - BUR\\_TN1010LF\\_LineArt](#)  
[Sales Drawings - 50094177](#)  
[Specifications - TN146LF](#)