

UC2W28L, Cast Copper Alloy Universal Parallel Clamp

By Burndy
Catalog # [UC2W28L](#)

Cast Copper Alloy Universal Parallel Clamp, 2 Sol. - 4/0 Str, 1-1/8 Length, 1-3/4 in Width, Tin-plated



Features

- Interlocking finger design accommodates large range of conductor sizes
- Tin-plated, cast of high copper alloy and clamped with plated steel bolt

Application

For All Combinations Of Copper, Aluminum, ACSR, 6201, 5005, Steel And Copperweld

Specifications

Buy American Compliant	No
Certification - cULus	No
EU RoHS Indicator	Yes
Certification - UL Recognized	No
Certification - ETL	No
Standards - RoHS Compliance Status	EX
Certification - CSA Approved	No
UL Listed	No

Conductor

Conductor - Galvanized Steel Str Size	9/32 (7) in;5/16 (7) in;3/8 (7) in;7/16 (7) in;1/2 (19) in;9/16 (19) in
Conductor - Galvanized Steel Str Size Range	9/32 (7) in-9/16 (19) in
Conductor - AAAC 5005 Size Range	77.47 (7) kcmil-246.9 (7) kcmil
Conductor - AAAC 6201 Size Range	77.47 (7) kcmil;123.3 (7) kcmil;155.4 (7) kcmil;195.7 (7) kcmil;246.9 (7) kcmil
Conductor - AAAC 6201 Size Range	77.47 (7) kcmil-246.9 (7) kcmil
Conductor - Copper Str Size	2 AWG;1 AWG;1/0 ;2/0 AWG;3/0 AWG;4/0 AWG
Conductor - AL Str Size	2 AWG;1 AWG;1/0 AWG;2/0 AWG;3/0 AWG;4/0 AWG
Conductor - AL Str Size Range	2 AWG-4/0 AWG
Conductor - Copper Solid Size	2 AWG
Conductor - Copper Solid Size Range	2 AWG
Conductor - Copper Str Size A	2 - 4/0

Conductor - Copper Str Size A Range	2 - 4/0
Conductor - Copper Str Size B Range	2 - 4/0
Conductor - Copper Str Size B Range	2 - 4/0
Conductor - Copper Str Size Range	2 AWG-4/0 AWG
Conductor - CopperWeld C Solid Size	8 AWG;7 AWG;6 AWG
Conductor - CopperWeld Solid Size Range	8 AWG-6 AWG
Conductor - AAAC 5005 Size	77.47 (7) kcmil;123.3 (7) kcmil;155.4 (7) kcmil;195.7 (7) kcmil;246.9 (7) kcmil

Dimensions

Dimension - Height fraction	1-1/2 in
Dimension - Height inch	1.50 in
Dimension - Height mm	0 mm
Dimension - Width fraction	1-3/4 in
Dimension - Width inch	1.75 in
Dimension - B Length fraction	1-1/8 in
Dimension - B Length inch	1.125 in

Force Related

Installation Torque Recommended in-lb	110 LBS/in
---------------------------------------	------------

General

Sub Brand	TAPIT
Plated	N
Type	UC-L, Universal
UPC 14 Digit GTIN	00781810094907
Plating Type	Tin - Electro Plated
UPC	781810094907

Logistics

Minimum Pack Quantity	1
Carton Quantity	50
Pallet Quantity	4200

Product Assets

[Catalog \[English\]](#)