



UC4W28

by Burndy
Catalog ID: UC4W28

Prop 65 Notice

CU Parallel Groove Clamp accommodates large number of CU Conductors, Conductor: 4 Sol. - 4/0 Str. (Either Groove).

Features: Type UC Connector Accommodates Large Range Of Conductors In Either Groove, Reducing Inventory To A Minimum, Interlocking Finger Design Provides Firm Grip With Maximum Contact Length, High Strength, Corrosion Resistant Silicone Bronze Hardware, One Wrench Installation, Width: 1-3/4 IN, Length: 2-1/8 IN, Height: 2 IN

Product Details

General

Application	For Range Of Copper
Installation Torque Recommended in-lb	240 LBS/in
Plated	N
Plating Type	Unplated
Sub Brand	TAPIT
Type	UC
UPC	781810012888

Dimensions

Dimension - B Length fraction	2-1/8 in
Dimension - B Length inch	2.125 in
Dimension - Height fraction	1-15/16 in
Dimension - Height inch	1.93 in
Dimension - Width fraction	1-3/4 in

Conductor Related

Conductor - Copper Solid Size	4 AWG
Conductor - Copper Solid Size Range	4 AWG
Conductor - Copper Str Size	4 AWG;3 AWG;2 AWG;1 AWG;1/0 ;2/0 AWG;3/0 AWG;4/0 AWG
Conductor - Copper Str Size A	4 - 4/0
Conductor - Copper Str Size A Range	4 - 4/0
Conductor - Copper Str Size B	4 - 4/0
Conductor - Copper Str Size B Range	4 - 4/0
Conductor - Copper Str Size Range	4 AWG-4/0 AWG

Certifications and Compliance

Certification - CSA Approved	No
Certification - ETL	No
Certification - UL Recognized	No
Certification - cULus	No

Standards - RoHS Compliance Status	EX
UL Listed	No

Logistics

Minimum Pack Quantity	2
-----------------------	---

For further technical assistance, please contact us

BURNDY Headquarters

47 East Industrial Park Drive
Manchester, New Hampshire 03109

Customer Service Hours:

8 AM - 8 PM Eastern Monday-Friday
Emergency Service 24-hours/365 Days
Phone: 1-800-346-4175
1-603-647-5299 (International)