


UC4W28, Copper Parallel Groove Clamp

By Burndy
Catalog # UC4W28



CU Parallel Groove Clamp accommodates large number of CU Conductors, Conductor: 4 Sol. - 4/0 Str. (Either Groove)

Features

- Type UC connector accommodates large range of conductors in either groove, reducing inventory requirements
- Interlocking finger design provides firm grip with maximum contact length
- High strength, corrosion resistant silicon bronze hardware

Application

For Range Of Copper

Specifications

Buy American Compliant	Contact Manufacturer
Certification - cULus	No
EU RoHS Indicator	Yes
Certification - UL Recognized	No
Buy America(n) Qualified	Contact Manufacturer
Certification - ETL	No
Standards - RoHS Compliance Status	EX
Certification - CSA Approved	No
UL Listed	No

Conductor

Conductor - Copper Str Size	<ul style="list-style-type: none"> • 4 AWG • 3 AWG • 2 AWG • 1 AWG • 1/0 • 2/0 AWG • 3/0 AWG • 4/0 AWG
Conductor - Copper Solid Size	4 AWG
Conductor - Copper Solid Size Range	4 AWG
Conductor - Copper Str Size A	4 - 4/0

Conductor - Copper Str Size A Range	4 - 4/0
Conductor - Copper Str Size B Range	4 - 4/0
Conductor - Copper Str Size B Range	4 - 4/0
Conductor - Copper Str Size Range	4 AWG-4/0 AWG

Dimensions

Dimension - Height fraction	1-15/16 in
Dimension - Height inch	1.93 in
Dimension - Height mm	50.8 mm
Dimension - Width fraction	1-3/4 in
Dimension - B Length fraction	2-1/8 in
Dimension - B Length inch	2.125 in

Force Related

Installation Torque Recommended in-lb	240 LBS/in
---------------------------------------	------------

General

Sub Brand	TAPIT
Plated	N
Type	UC
UPC 14 Digit GTIN	00781810012888
Plating Type	Unplated
UPC	781810012888

Logistics

Minimum Pack Quantity	2
Carton Quantity	4
Pallet Quantity	720

Product Assets

[Catalog \[English\]](#)