

UCK1UL, Tin-Plated Cast Copper Alloy Interlocking-Finger Design Parallel Clamp

By Burndy
Catalog # [UCK1UL](#)

Interlocking finger design accommodates large range of conductor sizes. Tin-plated, cast of high copper alloy and clamped with silicon bronze DURUM bolt, wrench size: 1/2.



Features

- Tin-plated cast copper alloy featuring interlocking-finger design
- Accommodates large range of conductor sizes
- Clamped with silicon bronze bolts

Application

For Use With Aluminum Or Galvanized Steel Strand To Copper Or Copper Bonded Steel Wire, Grounding For The Cable TV Industry

Specifications

Buy American Compliant	No
Certification - cULus	No
EU RoHS Indicator	Yes
Certification - UL Recognized	No
Certification - ETL	No
Standards - RoHS Compliance Status	CM
Certification - CSA Approved	No
UL Listed	Yes

Conductor

Conductor - Galvanized Steel Str Size Range	1/4 in -5/16 in
Conductor - Copper Solid Size B	6 Sol
Conductor - Copper Str Size B	6 Str

Dimensions

Dimension - L Length Overall mm	25 mm
Dimension - Height fraction	1-7/16 in
Dimension - Height inch	1.4375 in
Dimension - Height mm	36.5 mm
Dimension - Width fraction	1-7/16 in
Dimension - Width inch	1.4375 in
Dimension - Width mm	37 mm
Dimension - Length Overall inch	1 in

Force Related

Installation Torque Recommended in-lb	180 LBS/in
---------------------------------------	------------

General

Sub Brand	TAPIT
Plated	Y
Type	UC-K, Universal
UPC 12 Digit	781810120750
UPC 14 Digit GTIN	00781810120750
Material	Aluminum
Plating Type	Tin - Electro Plated
UPC	781810120750

Logistics

Minimum Pack Quantity	1
Carton Quantity	150
Pallet Quantity	1

Product Assets

[Catalog \[English\]](#)