

UCU28AC, Aluminum Mechanical Parallel Riser Tap Connector

By Burndy
Catalog # [UCU28AC](#)



Al Riser Tap(Polyethylene Connector Cover), #2-4/0 Str(Al/Cu Cable)(Run), #10 Sol-#2 Str(Al/Cu Cable)(Tap)

Features

- Parallel-groove riser tap with insulation cover for copper and aluminum
- Wide range-taking assembly for apartment house/light industrial applications
- Cover and connector are packaged together

Application

For Apartment House And Light Industrial Applications

Specifications

Buy American Compliant Certification - cULus	Contact Manufacturer
EU RoHS Indicator	No
Certification - UL Recognized	Yes
Industry Standard(s)	No
Buy America(n) Qualified	UL 486A-486B
Certification - ETL	Contact Manufacturer
Standards - Industry Standards Met	No
Standards - RoHS Compliance Status	UL 486A-486B
Certification - CSA Approved	CM
UL Listed	No
Certification - UL Listed Direct Burial	Yes
	No

Conductor

Conductor - AL Str Run	2 AWG;1 AWG;1/0 AWG;2/0 AWG;3/0 AWG;4/0 AWG
Conductor - AL Str Run Range	2 AWG-4/0 AWG
Conductor - AL Str Tap	8 AWG;6 AWG;4 AWG;3 AWG;2 AWG
Conductor - AL Str Tap Range	8 AWG-2 AWG
Conductor - Copper Solid Tap	10 AWG;9 AWG;8 AWG;7 AWG;6 AWG;5 AWG;4 AWG;3 AWG;2 AWG
Conductor - Copper Solid Tap Range	10 AWG-2 AWG
Conductor - Copper Str Run	2 AWG;1 AWG;1/0 ;2/0 AWG;3/0 AWG;4/0 AWG
Conductor - Copper Str Run Range	2 AWG-4/0 AWG
Conductor - Copper Str Tap	10 AWG;9 AWG;8 AWG;7 AWG;6 AWG;5 AWG;4 AWG;3

Conductor - Copper Str Tap Range	AWG;2 AWG
Conductor Type	10 AWG-2 AWG
	AL C Str-Run;CU C Str-Run;AL C Str-Tap;CU C Str-Tap;CU C Solid-Tap

Configuration

Connector Type	Riser Tap
----------------	-----------

Current

Rating - Minimum Voltage	600
--------------------------	-----

Dimensions

Dimension - L Length Overall mm	67 mm
Dimension - Height fraction	1-13/16 in
Dimension - Height inch	1.81 in
Dimension - Height mm	46 mm
Dimension - Screw Size inch	5/16
Dimension - Width fraction	2-1/4 in
Dimension - Width inch	2.24 in
Dimension - Width mm	57 mm
Dimension - Length Overall inch	2.62 in

Force Related

Installation Torque Recommended in-lb	120 LBS/in
---------------------------------------	------------

General

Sub Brand	TAPIT
Plated	N
Type	UCU-AC
UPC 12 Digit	781810006276
UPC 14 Digit GTIN	00781810006276
Material	Aluminum
Plating Type	Unplated
UPC	781810006276

Logistics

Minimum Pack Quantity	1
Carton Quantity	20
Pallet Quantity	3000



A Hubbell brand