

## UGSKIT2, Underground Connector Splice Kit

By Burndy  
Catalog # [UGSKIT2](#)

Watertight Underground Splice Kit, 8-2 AWG, w/ Two Heavy Wall Heat Shrink Sleeves, Al/Cu Rated



### Features

- Type UGSKIT are underground splice kits (watertight) for aluminum or copper
- Kit consists of a standard splice/reducer and includes heavy wall heat-shrink sleeve
- Dual rated for use with aluminum and copper
- Connector is installed with common installation tools
- Both heavy wall heat shrink sleeves are lined with adhesive material providing a watertight splice

### Application

For All Aluminum or Copper/Aluminum Combinations, UF Direct Burial

### Specifications

Buy American Compliant	No
Certification - cULus	No
EU RoHS Indicator	Yes
Certification - UL Recognized	No
Industry Standard(s)	UL486D
Certification - ETL	No
Standards - Industry Standards Met	UL486D
Standards - RoHS Compliance Status	CM
Certification - CSA Approved	Yes
UL Listed	Yes
Certification - UL Listed Direct Burial	Yes

### Conductor

Conductor - Copper Str Size	8 AWG;7 AWG;6 AWG;5 AWG;4 AWG;3 AWG;2 AWG
Conductor - AL Str Size	8 AWG;6 AWG;4 AWG;3 AWG;2 AWG
Conductor - AL Str Size Range	8 AWG-2 AWG
Conductor Size	8-2 AWG

Conductor - Copper Str Size Range 8 AWG-2 AWG

### Configuration

Connector Type Splice/Heat Shrink Kit

### Current

Rating - Minimum Voltage 600

### Dimensions

Dimension - L Length Overall mm	35 mm
Dimension - Height mm	0 mm
Hex Size	Slot
Dimension - Length Overall inch	1.38 in

### General

Sub Brand	SPLICE KIT
Physical Attribute - Screw Type	Allen
Plated	N
Type	UGSKIT, Watertight/Underground
UPC 14 Digit GTIN	00781810175279
Material	Aluminum
Plating Type	Unplated
UPC	781810175279

### Logistics

Minimum Pack Quantity	1
Carton Quantity	10
Pallet Quantity	1050

### Operational

Temperature Rating 194

### Product Assets

[Catalog \[English\]](#)