


Y2928R, Compression Splice Reducer, Barrel 250 kcmil, Barrel B 4/0 AWG

By Burndy
Catalog # [Y2928R](#)



Reducing Adapter for 250 kcmil Barrel Reducing down to 4/0 AWG CU

Features

- Copper reducing sleeve that allows a larger terminal or splice to accommodate a smaller wire gauge

Application

Wire Reducing Splice Adapter Insert

Specifications

Buy American Compliant	Contact Manufacturer
Certification - cULus	No
EU RoHS Indicator	Yes
Certification - UL Recognized	No
Buy America(n) Qualified	Contact Manufacturer
Certification - ETL	No
Standards - RoHS Compliance Status	CM
Certification - CSA Approved	No
UL Listed	No

Conductor

Conductor - Material	COPPER
Wire Size	#4/0 AWG
Conductor - Copper Str Run	250 kcmil
Conductor - Copper Str Run Range	250 kcmil
Conductor - Copper Str Size Range	4/0 AWG
Conductor - Copper Str Tap	4/0 AWG
Conductor - Copper Str Tap Range	4/0 AWG
Conductor Type	CODE

Configuration

Connector Type	LONG BARREL
----------------	-------------

Current

Voltage - Maximum	35000
-------------------	-------

Dimensions

Dimension - Outside Diameter inch	0.592 in
Dimension - L Length Overall mm	41 mm
Dimension - B Length inch	1.62 in
Dimension - Length Overall inch	1.62 in

General

Die Index	16
Sub Brand	REDUCER/ADAPTER
Color Code	Yellow
Plated	Y
Feature - Barrel Type	Long
Type	Y-R, Compression
UPC 12 Digit	781810085196
UPC 14 Digit GTIN	00781810085196
Material	COPPER
Plating Type	Tin - Electro Plated
Finish Type	Tin-Plated
UPC	781810085196

Logistics

Minimum Pack Quantity	1
Carton Quantity	100
Pallet Quantity	39200

Operational

Temperature Rating	194
--------------------	-----

Product Assets

[Catalog \[English\]](#)