


Y3432R, Compression Splice Reducer, Barrel A 500 kcmil, Barrel B 400 kcmil

By Burndy
Catalog # [Y3432R](#)



Reducing Adapter for 500 kcmil Barrel Reducing down to 400 kcmil CU

Features

- Copper reducing sleeve that allows a larger terminal or splice to accommodate a smaller wire gauge

Application

Wire Reducing Splice Adapter Insert

Specifications

Buy American Compliant	Contact Manufacturer
Certification - cULus	No
EU RoHS Indicator	Yes
Certification - UL Recognized	No
Buy America(n) Qualified	Contact Manufacturer
Certification - ETL	No
Standards - RoHS Compliance Status	CM
Certification - CSA Approved	No
UL Listed	No

Conductor

Conductor - Material	COPPER
Wire Size	400 kcmil
Conductor - Copper Str Run	500 kcmil
Conductor - Copper Str Run Range	500 kcmil
Conductor - Copper Str Size Range	2 AWG
Conductor - Copper Str Tap	400 KCMIL
Conductor - Copper Str Tap Range	400 kcmil
Conductor Type	CODE

Configuration

Connector Type	LONG BARREL
----------------	-------------

Current

Voltage - Maximum	35000
-------------------	-------

Dimensions

Dimension - Outside Diameter inch	0.821 in
Dimension - L Length Overall mm	64 mm
Dimension - B Length inch	2.50 in
Dimension - Length Overall inch	2.50 in

General

Die Index	20
Sub Brand	REDUCER/ADAPTER
Color Code	Brown
Plated	Y
Feature - Barrel Type	Long
Type	Y-R, Compression
UPC 12 Digit	781810001110
UPC 14 Digit GTIN	00781810001110
Material	COPPER
Plating Type	Tin Plated
Finish Type	Tin-Plated
UPC	781810001110

Logistics

Minimum Pack Quantity	1
Carton Quantity	50
Pallet Quantity	14800

Operational

Temperature Rating	194
--------------------	-----

Product Assets

[Catalog \[English\]](#)