



6-Ton Latch Head Crimper, Self Contained Hydraulic, Permanent D3 Groove (no die needed), Uses W and X Dies

By Burndy
Catalog # Y500CTHS



6T Latch Head Crimper, D3 Groove.

Features

- Permanent functional D3 groove (no die needed)
- Used with W, X, and W-VT style dies
- 180° head rotation
- Enhanced clearance for tap connectors

Application

Crimping

General

Application - For Use On	Copper, Aluminum, ACSR, Steel, Copperweld, Alumoweld, 6201, 5005, Compressed, Compact, Stranded and Solid Conductors
Catalog Number	Y500CTHS
Crimp Force Capacity	6 ton
Die Type	W Die and X Die
EU RoHS Indicator	Yes
Sub Brand	HYPRESS
Tool Type	Self-Contained Hydraulic Crimper
Trade Name	HYPRESS™
UPC	781810270387
UPC 14 Digit GTIN	00781810270387

Dimensions

Dimensions	18 in x 5.5 in x 2.68 in
Height	2.68 in
Length	18 in
Weight	7.8 lb

Width 5.5 in

Conductor Related

Crimping Ranges	Copper, Aluminum, ACSR, Steel, Copperweld, Alumoweld, 6201, 5005, Compressed, Compact, Stranded and Solid conductors, Installs Splices, Taps or Terminations: #8 - 600 kcmil Copper Str., #8 - 350 kcmil Flex, #8 - 350 kcmil Aluminum
-----------------	--

Certifications And Compliance

Buy America(n) Qualified	TAA Compliant (All status valid till December 2024)
Standards - RoHS Compliance Status	EX

Logistics

Minimum Pack Quantity	1
Package Contents	Tool, Plastic Case

Product Assets

- [Catalogs - BURNDY Master Catalog - Section N - Tooling](#)
- [Catalogs - BURNDY Master Catalog - Full Line BURNDY Catalog](#)
- [Customer Notices - Prop 65 Notice](#)
- [Interactive Catalog - BURNDY Full-Line Digital Catalog](#)
- [Product Cross Section Image\(s\) - BUR_082_OXCF_Y500CTHS_lineart](#)
- [Sales Drawings - 2142201](#)
- [Specifications - Y500CTHS](#)