**BURNDY®**

# YA26LNT38, Compression Terminal, 2/0 AWG Cu, 1-Hole, 3/8" Stud, Narrow Tongue

By Burndy
Catalog # YA26LNT38

2/0 AWG, CU, 1 Hole, 3/8 Stud, Standard Barrel, Inspection WIndow, Narrow Tongue

## Features

- Barrel designed with internal chamfer at wire entry for smooth insertion of wire, preventing possible damage of the strands
- Standard barrel length is recommended for installations with limited space availability
- Electro-tin plated unless otherwise specified to reduce galvanic corrosion (bimetallic) and resist corrosive elements
- Connectors are clearly marked with stamping and barrel color coding

## Application

Wire Termination

## Specifications

| | |
|---|---|
| Buy American Compliant | Contact Manufacturer |
| Certification - cULus | No |
| EU RoHS Indicator | Yes |
| Certification - UL Recognized | No |
| Industry Standard(s) | UL 486A-486B |
| Buy America(n) Qualified | Contact Manufacturer |
| Certification - ETL | No |
| Standards - RoHS Compliance Status | CM |
| Certification - CSA Approved | Yes |
| UL Listed | Yes |

## Conductor

| | |
|---|---|
| Conductor - Material | COPPER |
| Conductor - Copper Str Size | 2/0 AWG |
| Conductor - Copper DLO Size Range | N/A |
| Conductor - Copper Str Navy Size | 125 (61) Navy |
| Conductor - Copper Str Navy Size Range | 125 (61) Navy |
| Conductor Size | 2/0 AWG |
| Conductor - Copper Str Size Range | 2/0 AWG |
| Conductor Type | CODE |

## Configuration

| | |
|---|---|
| Physical Attribute - Number of Holes | 1 |
| Connector Type | STANDARD BARREL |

## Current

| | |
|---|---|
| Voltage - Maximum | 35000 |
| Voltage Rating | 35 kV |

## Dimensions

| | |
|---|---|
| Dimension - Outside Diameter inch | 0.56 in |
| Dimension - L Length Overall mm | 63 mm |
| Dimension - Pad Width inch | 0.72 in |
| Dimension - Hole Size fraction | 3/8 |
| Dimension - Hole Size inch | 0.41 |
| Dimension - Hole Size mm | 10.4 mm |
| Dimension - Strip Length inch | 1 in |
| Dimension - Stud Size fraction | 3/8 |
| Dimension - Stud Size inch | 3/8 |
| Dimension - Thread Size | 3/8 |
| Dimension - B Length fraction | 15/16 in |
| Dimension - B Length inch | 0.94 in |
| Dimension - Z inch | 0.62 in |
| Physical Attribute - Tongue Angle | Straight |
| Dimension - Bolt Hole Size inch | 0.39 in |
| Dimension - Bolt Size fraction | 3/8 |
| Dimension - Bolt Size inch | 0.38 |
| Dimension - Length Overall inch | 2.48 in |
| Dimension - D inch | 1.00 in |
| Dimension - N inch | 0.38 in |

## General

| | |
|---|---|
| Die Index | 13 |
| Trade Name | HYLUG™ |
| Sub Brand | TERMINALS, HYLUG |
| Color Code | Black |
| Plated | Y |
| Feature - Barrel Type | Standard |
| Feature - Barrel Style | Chamfered |
| Type | YA-L-NT |
| UPC 14 Digit GTIN | 00781810035931 |
| Material | COPPER |
| Plating Type | Tin - Electro Plated |
| Finish Type | Tin-Plated |
| UPC | 781810035931 |

## Logistics

| | |
|---|---|
| Minimum Pack Quantity | 1 |
| Carton Quantity | 100 |
| Pallet Quantity | 34800 |

## Product Assets

Catalog [English]

Installation Manual [English]

Installation Manual [French, English]

A Hubbell brand