

## YA28A7, Compression Terminal, 4/0 AWG Al, 2-Hole, 3/8" Stud, 1" Spacing

By Burndy

Catalog # [YA28A7](#)

4/0 AWG, AL, 2 Hole, 3/8" Stud 1" Hole Spacing, AL9CU



### Features

- UL486A-486B Listed and CSA Certified
- Aluminum terminals are dual rated to accommodate both copper and aluminum wire and are indicated with AL-CU on the connector - AL9CU is UL Listed 90°C, up to 35kV, AL7CU is UL Listed 75°C, up to 35kV
- Barrel is designed with an internal chamfer at the wire entry to ensure smooth insertion of the wire, preventing possible damage of the wire strands during insertion
- Electro-tin plated unless otherwise specified to reduce galvanic corrosion (bimetallic) and resist corrosive elements
- Connectors are clearly marked with wire size, die index, color code, and crimp location bands
- Factory pre-filled with PENETROX Type A13 oxide inhibitor
- Color coded end caps are factory inserted in the barrels to match the die color code and prevent foreign materials from entering the barrel
- Aluminum oxidation is not easily detected but causes resistance in a connection, it is imperative the proper preparation takes place prior to making an aluminum-to-aluminum connection

### Application

Wire Termination

### Specifications

Buy American Compliant	Contact Manufacturer
Certification - cULus	No
EU RoHS Indicator	Yes
Certification - UL Recognized	No
Industry Standard(s)	UL 486A-486B
Buy America(n) Qualified	Contact Manufacturer
Certification - ETL	No
Standards - Industry Standards Met	UL 486A-486B
Standards - RoHS Compliance Status	CM
Certification - CSA Approved	Yes
UL Listed	Yes

### Conductor

Conductor - Material	ALUMINUM / COPPER
Wire Size	4/0 AWG
Conductor - Copper Str Size	4/0 AWG
Conductor - AL Str Size	4/0 AWG

Conductor - AL Str Size Range	4/0 AWG
Conductor - Copper Solid Size	4/0 AWG
Conductor - Copper Solid Size Range	4/0 AWG
Conductor Size	4/0 AWG
Conductor - Copper Str Size Range	4/0 AWG
Conductor Type	CODE

### Configuration

Physical Attribute - Number of Holes	2
Connector Type	DUAL RATED

### Current

Voltage - Maximum	35000
Voltage Rating	35 kV

### Dimensions

Dimension - Outside Diameter inch	0.85 in
Dimension - L Length Overall mm	101 mm
Dimension - Pad Width inch	1.17 in
Dimension - Hole Size fraction	3/8
Dimension - Hole Size inch	0.41
Dimension - Hole Size mm	10.4 mm
Dimension - Strip Length inch	1-5/8
Dimension - Stud Size fraction	3/8
Dimension - Stud Size inch	3/8
Dimension - Thread Size	3/8
Dimension - B Length fraction	1-3/8 in
Dimension - B Length inch	1.39 in
Dimension - Z inch	0.45 in
Physical Attribute - Tongue Angle	Straight
Dimension - Bolt Hole Size inch	0.39 in
Dimension - Bolt Size fraction	3/8
Dimension - Bolt Size inch	0.38
Dimension - Length Overall inch	3.97 in
Dimension - D inch	1.89 in
Dimension - N inch	0.44 in

### General

Die Index	298
Trade Name	HYLUG™
Sub Brand	HYLUG
Color Code	White
Physical Attribute - Tongue Type	Standard
Plated	Y
Feature - Barrel Type	Standard
Feature - Barrel Style	Chamfered
Type	YA-A, Dual Rated
UPC 12 Digit	781810023464
UPC 14 Digit GTIN	00781810023464
Material	ALUMINUM
Plating Type	Tin - Electro Plated
Finish Type	Tin-Plated

UPC 781810023464

### Logistics

Minimum Pack Quantity	10
Carton Quantity	60
Pallet Quantity	3840

### Operational

Temperature Rating	194
--------------------	-----

### Product Assets

- [Catalog \[English\]](#)
- [Installation Manual \[English\]](#)
- [Installation Manual \[English\]](#)



A Hubbell brand