



YA32L2NTCFX, Compression Terminal, 300 kcmil G,H,I,K,M, 313 DLO, Cu, 2-Hole, 1/2" Stud, 1-3/4" Spacing, Standard Barrel

By Burndy

Catalog # [YA32L2NTCFX](#)

300 kcmil G,H,I,K,M,313 DLO, CU, 2 Hole, 1/2 Stud, 1-3/4 IN Spacing, Standard Barrel, Inspection Window

Features

- Barrel designed with internal chamfer at wire entry for smooth insertion of wire, preventing possible damage of the strands
- Standard barrel length is recommended for installations with limited space availability
- Electro-tin plated unless otherwise specified to reduce galvanic corrosion (bimetallic) and resist corrosive elements
- Connectors are clearly marked with stamping and barrel color coding
- 2-Hole design prevents rotation

Application

Wire Termination

Specifications

Buy American Compliant	Contact Manufacturer
Certification - cULus	No
EU RoHS Indicator	Yes
Certification - UL Recognized	No
Industry Standard(s)	UL 486A-486B
Buy America(n) Qualified	Contact Manufacturer
Certification - ETL	No
Standards - RoHS Compliance Status	CM
Certification - CSA Approved	Yes
UL Listed	Yes

Conductor

Conductor - Material	COPPER
Wire Size	300 KCMIL
Conductor - Copper Str Size	300 KCMIL
Conductor - Copper Flex I Size Range	300 kcmil
Conductor - Copper Flex K Size	300 KCMIL
Conductor - Copper Flex K Size Range	300 kcmil
Conductor - Copper Flex M Size	300 KCMIL
Conductor - Copper DLO Size	313 KCMIL
Conductor - Copper DLO Size Range	313 kcmil
Conductor - Copper Flex G Size	300 KCMIL
Conductor - Copper Flex G Size Range	300 kcmil



Conductor - Copper Flex H Size	300 KCMIL
Conductor Size	300 KCMIL
Conductor - Copper Str Size Range	300 kcmil
Conductor - Copper Flex H Size Range	300 kcmil
Conductor Type	FLEX
Conductor - Copper Flex I Size	300 KCMIL

Configuration

Physical Attribute - Number of Holes	2
Connector Type	STANDARD BARREL

Current

Voltage - Maximum	35000
Voltage Rating	35 kV

Dimensions

Dimension - Outside Diameter inch	0.95 in
Dimension - L Length Overall mm	124 mm
Dimension - Pad Width inch	1.40 in
Dimension - Height mm	0 mm
Dimension - Hole Size fraction	1/2
Dimension - Hole Size inch	0.56
Dimension - Hole Size mm	14 mm
Dimension - Strip Length inch	1-1/4
Dimension - Stud Size fraction	1/2
Dimension - B Length fraction	1-3/16 in
Dimension - B Length inch	1.19 in
Dimension - Z inch	0.65 in
Physical Attribute - Tongue Angle	Straight
Dimension - Bolt Hole Size inch	0.56 in
Dimension - Bolt Size fraction	1/2
Dimension - Bolt Size inch	0.5
Dimension - Length Overall inch	4.88 in
Dimension - N inch	0.63 in

General

Die Index	18
-----------	----

Trade Name	HYLUG™	Finish Type	Tin-Plated
Sub Brand	HYLUG	UPC	781810020159
Color Code	Red		
Physical Attribute - Tongue	Standard	Logistics	
Type		Minimum Pack Quantity	1
Plated	Y	Carton Quantity	25
Feature - Barrel Type	Standard	Pallet Quantity	5550
Feature - Barrel Style	Chamfered		
Type	Standard Barrel, Tin Plated	Product Assets	
UPC 12 Digit	781810020159	Catalog [English]	
UPC 14 Digit GTIN	00781810020159	Installation Manual [English]	
Material	COPPER	Installation Manual [English]	
Plating Type	Tin		



A Hubbell brand