



YA34L2TC38FX

by Burndy
Catalog ID: YA34L2TC38FX

Prop65

Copper Compression Lug, 2 Hole w/ Inspection Window, 373.7 Flex, 3/8" Stud, 1" Stud Hole Spacing, Short Barrel, Tin Plated.

Features: UL Listed 90 DEG C, 600 V - 35 KV, 45 DEG And 90 DEG Angles Are Available, Temperature Rating: 90 DEG C, Finish: Electro-Tin Plated, Tongue Angle: Straight, Die Index: 19, Wire Strip Length: 1-1/4 IN, Color Code: Blue, Tools, Die Set Catalog Number, And (number Of Crimps): Mechanical: MD6, OUR840, MD7-34R Tool, W32VT Die, (2), Hydraulic: BCT500HS, Y500CTHS Tool, W32VT, W32RT Die, (2), Y35, Y39, Y750, PAT750 Tool, U32RT Die, (2), Y46 Tool, U32RT Die With PUADP-1 Adapter, (2), Dieless Tools (number Of Crimps): Y644HS, Y81KFT, Y81KFTMBH, PAT81KFT-18V Tool, (1), Conductor Type: Flexible Copper

Product Details

General

| | |
|--------------------------------------|-----------------------------|
| Application | For Flex Conductor |
| Color Code | Blue |
| Connector Type | Terminal |
| Die Index | 19;470 |
| Feature - Barrel Style | Chamfered |
| Feature - Barrel Type | Standard |
| Material | Copper |
| Physical Attribute - Number of Holes | 2 |
| Physical Attribute - Tongue Type | Standard |
| Plated | Y |
| Plating Type | Tin |
| Sub Brand | HYLUG |
| Trade Name | HYLUG™ |
| Type | Standard Barrel, Tin Plated |
| UPC | 781810018941 |
| UPC 12 Digit | 7818100189411 |

Dimensions

| | |
|---------------------------------|----------|
| Dimension - B Length fraction | 1-1/4 in |
| Dimension - B Length inch | 1.27 in |
| Dimension - Bolt Hole Size inch | 0.39 in |
| Dimension - Bolt Size fraction | 3/8 |
| Dimension - Hole Size inch | 0.41 in |
| Dimension - Hole Size mm | 10 mm |
| Dimension - L Length Overall mm | 99 mm |
| Dimension - Length Overall inch | 3.88 in |

| | |
|-----------------------------------|----------|
| Dimension - N inch | 0.41 in |
| Dimension - Outside Diameter inch | 1.06 in |
| Dimension - Pad Width inch | 1.55 in |
| Dimension - Strip Length inch | 1-5/16 |
| Dimension - Z inch | 0.42 in |
| Physical Attribute - Tongue Angle | Straight |

Electrical Ratings

| | |
|--------------------------|-------|
| Rating - KVA | 35 kV |
| Rating - Minimum Voltage | 600 |
| Voltage - Maximum | 35000 |

Conductor Related

| | |
|--------------------------------------|---------------------|
| Conductor - Copper DLO Size | 373.7 (925/#24) DLO |
| Conductor - Copper DLO Size Range | 373.7 (925/#24) DLO |
| Conductor - Copper Flex G Size | 350 kcmil |
| Conductor - Copper Flex G Size Range | 350 kcmil |
| Conductor - Copper Flex H Size | 350 kcmil |
| Conductor - Copper Flex H Size Range | 350 kcmil |
| Conductor - Copper Flex I Size | 350 kcmil |
| Conductor - Copper Flex I Size Range | 350 kcmil |
| Conductor - Copper Flex K Size | 350 kcmil |
| Conductor - Copper Flex K Size Range | 350 kcmil |
| Conductor - Copper Flex M Size | 350 kcmil |
| Conductor - Copper Flex M Size Range | 350 kcmil |
| Conductor - Material | Copper |

Certifications and Compliance

| | |
|------------------------------------|-----|
| Certification - CSA Approved | No |
| Certification - ETL | No |
| Certification - UL Recognized | No |
| Certification - cULus | No |
| Standards - RoHS Compliance Status | CM |
| UL Listed | Yes |

Logistics

| | |
|-----------------------|---|
| Minimum Pack Quantity | 1 |
|-----------------------|---|

For further technical assistance, please contact us

BURNDY Headquarters
 47 East Industrial Park Drive
 Manchester, New Hampshire 03109

Customer Service Hours:
 8 AM - 8 PM Eastern Monday-Friday
 Emergency Service 24-hours/365 Days
 Phone: 1-800-346-4175
 1-603-647-5299 (International)