



# YA34L2TC38FX, 350 kcmil G,H,I,K,M,373 DLO, CU, 2 Hole, 3/8 Stud, 1" Spacing, Standard Barrel, Inspection Window

By Burndy  
Catalog # [YA34L2TC38FX](#)



350 kcmil G,H,I,K,M,373 DLO, CU, 2 Hole, 3/8 Stud, 1 IN Spacing, Standard Barrel, Inspection Window

## Features

- Barrel designed with internal chamfer at wire entry for smooth insertion of wire, preventing possible damage of the strands
- Standard barrel length is recommended for installations with limited space availability
- Electro-tin plated unless otherwise specified to reduce galvanic corrosion (bimetallic) and resist corrosive elements
- Connectors are clearly marked with stamping and barrel color coding
- 2-Hole design prevents rotation

## Application

Wire Termination

## Specifications

Buy American Compliant	No
Certification - cULus	No
EU RoHS Indicator	Yes
Certification - UL Recognized	No
Industry Standard(s)	UL 486A-486B
Certification - ETL	No
Standards - RoHS Compliance Status	CM
Certification - CSA Approved	Yes
UL Listed	Yes

## Conductor

Conductor - Material	COPPER
Wire Size	350 KCMIL
Conductor - Copper Str Size	350 KCMIL
Conductor - Copper Flex I Size Range	350 kcmil
Conductor - Copper Flex K Size	350 KCMIL
Conductor - Copper Flex K Size Range	350 kcmil
Conductor - Copper Flex M Size	350 KCMIL
Conductor - Copper Flex M Size Range	350 kcmil
Conductor - Copper DLO Size	373 KCMIL
Conductor - Copper DLO Size Range	373 kcmil
Conductor - Copper Flex G Size	350 KCMIL

Conductor - Copper Flex G Size Range	350 kcmil
Conductor - Copper Flex H Size Conductor Size	350 KCMIL
Conductor - Copper Str Size Range	350 kcmil
Conductor - Copper Flex H Size Range	350 kcmil
Conductor Type	FLEX
Conductor - Copper Flex I Size	350 KCMIL

## Configuration

Physical Attribute - Number of Holes	2
Connector Type	STANDARD BARREL

## Current

Voltage - Maximum	35000
Voltage Rating	35 kV

## Dimensions

Dimension - Outside Diameter inch	1.06 inch
Dimension - L Length Overall mm	99 mm
Dimension - Pad Width inch	1.55 inch
Dimension - Height mm	0 mm
Dimension - Hole Size fraction	3/8
Dimension - Hole Size inch	0.41
Dimension - Hole Size mm	10.4 mm
Dimension - Strip Length inch	1-5/16
Dimension - Stud Size fraction	3/8
Dimension - B Length fraction	1-1/4 in
Dimension - B Length inch	1.27 in
Dimension - Z inch	0.42 in
Physical Attribute - Tongue Angle	Straight
Dimension - Bolt Hole Size inch	0.39 in
Dimension - Bolt Size fraction	3/8
Dimension - Bolt Size inch	0.38
Dimension - Length Overall inch	3.88 in
Dimension - N inch	0.41 in

## General

Die Index	19
Trade Name	HYLUG™
Sub Brand	HYLUG
Color Code	Blue
Physical Attribute - Tongue Type	Standard
Plated	Y
Feature - Barrel Type	Standard
Feature - Barrel Style Type	Chamfered
UPC 12 Digit	Standard Barrel, Tin Plated
UPC 14 Digit GTIN	781810018941
Material	00781810018941
	COPPER

Plating Type	Tin
Finish Type	Tin-Plated
UPC	781810018941

### Logistics

Minimum Pack Quantity	1
Carton Quantity	50
Pallet Quantity	4800

### Product Assets

- [Catalog \[English\]](#)
- [Installation Manual \[English\]](#)
- [Installation Manual \[English\]](#)



A Hubbell brand