

YA392LN, Compression Terminal, 750 kcmil Cu, 2-Hole, 1/2" Stud, 1-3/4" Spacing

By Burndy
Catalog # [YA392LN](#)

750 kcmil, CU, 2 Hole, 1/2 Stud, 1-3/4 IN Spacing, Standard Barrel, Inspection Window



Features

- Barrel designed with internal chamfer at wire entry for smooth insertion of wire, preventing possible damage of the strands
- Standard barrel length is recommended for installations with limited space availability
- Electro-tin plated unless otherwise specified to reduce galvanic corrosion (bimetallic) and resist corrosive elements
- Connectors are clearly marked with stamping and barrel color coding
- 2-Hole design prevents rotation

Application

Wire Termination

Specifications

| | |
|------------------------------------|--------------|
| Buy American Compliant | No |
| Certification - cULus | No |
| EU RoHS Indicator | Yes |
| Certification - UL Recognized | No |
| Industry Standard(s) | UL 486A-486B |
| Certification - ETL | No |
| Standards - RoHS Compliance Status | CM |
| Certification - CSA Approved | Yes |
| UL Listed | Yes |

Conductor

| | |
|-----------------------------------|-----------|
| Conductor - Material | COPPER |
| Conductor - Copper Str Size | 750 KCMIL |
| Conductor - Copper DLO Size Range | N/A |
| Conductor Size | 750 KCMIL |
| Conductor - Copper Str Size Range | 750 kcmil |
| Conductor Type | CODE |

Configuration

| | |
|--------------------------------------|-----------------|
| Physical Attribute - Number of Holes | 2 |
| Connector Type | STANDARD BARREL |

Current

| | |
|-------------------|-------|
| Voltage - Maximum | 35000 |
|-------------------|-------|

| | |
|----------------|-------|
| Voltage Rating | 35 kV |
|----------------|-------|

Dimensions

| | |
|-----------------------------------|-----------|
| Dimension - Outside Diameter inch | 1.30 in |
| Dimension - L Length Overall mm | 136 mm |
| Dimension - Pad Width inch | 1.91 in |
| Dimension - Hole Size fraction | 1/2 |
| Dimension - Hole Size inch | 0.56 |
| Dimension - Hole Size mm | 14 mm |
| Dimension - Strip Length inch | 1-15/16 |
| Dimension - Stud Size fraction | 1/2 |
| Dimension - Stud Size inch | 1/2 |
| Dimension - B Length fraction | 1-7/16 in |
| Dimension - B Length inch | 1.42 in |
| Dimension - Z inch | 0.64 in |
| Physical Attribute - Tongue Angle | Straight |
| Dimension - Bolt Hole Size inch | 0.52 in |
| Dimension - Bolt Size fraction | 1/2 |
| Dimension - Bolt Size inch | 0.5 |
| Dimension - Length Overall inch | 5.36 in |
| Dimension - D inch | 3.02 in |
| Dimension - N inch | 0.63 in |

General

| | |
|----------------------------------|-----------------------------|
| Die Index | 24 |
| Trade Name | HYLUG™ |
| Sub Brand | HYLUG |
| Color Code | Black |
| Physical Attribute - Tongue Type | Standard |
| Plated | Y |
| Feature - Barrel Type | Standard |
| Feature - Barrel Style | Chamfered;Skived |
| Type | Standard Barrel, Tin Plated |
| UPC 14 Digit GTIN | 00781810522073 |
| Material | COPPER |
| Plating Type | Tin - Electro Plated |
| Finish Type | Tin-Plated |
| UPC | 781810522073 |

Logistics

| | |
|-----------------------|---|
| Minimum Pack Quantity | 1 |
|-----------------------|---|

Product Assets

[Catalog \[English\]](#)

[Installation Manual \[English\]](#)

[Installation Manual \[French, English\]](#)



A Hubbell brand