

YA39L, Compression Terminal, 750 kcmil Cu, 1-Hole, 5/8" Stud, Standard Barrel

By Burndy
Catalog # [YA39L](#)



750 kcmil, CU, 1 Hole, 5/8 Stud, Standard Barrel, Inspection Window

Features

- Barrel designed with internal chamfer at wire entry for smooth insertion of wire, preventing possible damage of the strands
- Standard barrel length is recommended for installations with limited space availability
- Electro-tin plated unless otherwise specified to reduce galvanic corrosion (bimetallic) and resist corrosive elements
- Connectors are clearly marked with stamping and barrel color coding

Application

Wire Termination

Specifications

Buy American Compliant	No
Certification - cULus	No
EU RoHS Indicator	Yes
Certification - UL Recognized	No
Industry Standard(s)	UL 486A-486B
Certification - ETL	No
Standards - Industry Standards Met	UL467
Standards - RoHS Compliance Status	CM
Certification - CSA Approved	Yes
UL Listed	Yes

Conductor

Conductor - Material	COPPER
Conductor - Copper Str Size	750 KCMIL
Conductor - Copper DLO Size Range	N/A
Conductor Size	750 KCMIL
Conductor - Copper Str Size Range	750 kcmil
Conductor Type	CODE

Configuration

Physical Attribute - Number of Holes	1
Connector Type	STANDARD BARREL

Current

Voltage - Maximum	35000
Voltage Rating	35 kV

Dimensions

Dimension - Outside Diameter inch	1.30 in
Dimension - L Length Overall mm	91 mm
Dimension - Pad Width inch	1.91 in
Dimension - Hole Size fraction	5/8
Dimension - Hole Size inch	0.69
Dimension - Hole Size mm	17.5 mm
Dimension - Strip Length inch	1-15/16
Dimension - Stud Size fraction	5/8
Dimension - Stud Size inch	5/8
Dimension - B Length fraction	1-7/16 in
Dimension - B Length inch	1.42 in
Dimension - Z inch	0.67 in
Physical Attribute - Tongue Angle	Straight
Dimension - Bolt Hole Size inch	0.66 in
Dimension - Bolt Size fraction	5/8
Dimension - Bolt Size inch	0.63
Dimension - Length Overall inch	3.57 in
Dimension - D inch	1.33 in
Dimension - N inch	0.66 in

General

Die Index	24
Trade Name	HYLUG™
Sub Brand	HYLUG
Color Code	Black
Physical Attribute - Tongue Type	Standard
Plated	Y
Feature - Barrel Type	Standard
Feature - Barrel Style	Chamfered;Skived
Type	Standard Barrel, Tin Plated
UPC 14 Digit GTIN	00781810522653
Material	COPPER
Plating Type	Tin - Electro Plated
Finish Type	Tin-Plated
UPC	781810522653

Logistics

Minimum Pack Quantity 1
Carton Quantity 6

Product Assets

[Catalog \[English\]](#)

[Installation Manual \[English\]](#)

[Installation Manual \[French, English\]](#)



A Hubbell brand

© 2025 Hubbell Incorporated. All rights reserved
BRDY-YA39L-SPEC-EN | REV 11/2025