



## YA39L2TC38, Compression Terminal, 750 kcmil Cu, 2-Hole, 3/8" Stud, 1" Spacing, Standard Barrel

By Burndy  
Catalog # [YA39L2TC38](#)

750 kcmil, CU, 2 Hole, 3/8 Stud, 1 IN Spacing, Standard Barrel, Inspection Window



### Features

- Barrel designed with internal chamfer at wire entry for smooth insertion of wire, preventing possible damage of the strands
- Standard barrel length is recommended for installations with limited space availability
- Electro-tin plated unless otherwise specified to reduce galvanic corrosion (bimetallic) and resist corrosive elements
- Connectors are clearly marked with stamping and barrel color coding
- 2-Hole design prevents rotation

### Application

Wire Termination

### Specifications

Buy American Compliant	No
Certification - cULus	No
EU RoHS Indicator	Yes
Certification - UL Recognized	No
Industry Standard(s)	UL 486A-486B
Certification - ETL	No
Standards - Industry Standards Met	UL 486A-486B
Standards - RoHS Compliance Status	CM
Certification - CSA Approved	Yes
UL Listed	Yes

### Conductor

Conductor - Material	COPPER
Conductor - Copper Str Size	750 KCMIL
Conductor - Copper DLO Size Range	N/A
Conductor Size	750 KCMIL
Conductor - Copper Str Size Range	750 kcmil
Conductor Type	CODE

### Configuration

Physical Attribute - Number of Holes	2
Connector Type	STANDARD BARREL

### Current

Voltage - Maximum	35000
Voltage Rating	35 kV

### Dimensions

Dimension - Outside Diameter inch	1.30 in
Dimension - L Length Overall mm	111 mm
Dimension - Pad Width inch	1.91 in
Dimension - Hole Size fraction	3/8
Dimension - Hole Size inch	0.41
Dimension - Hole Size mm	10.4 mm
Dimension - Strip Length inch	1-15/16
Dimension - Stud Size fraction	3/8
Dimension - Stud Size inch	3/8
Dimension - B Length fraction	1-7/16 in
Dimension - B Length inch	1.42 in
Dimension - Z inch	0.52 in
Physical Attribute - Tongue Angle	Straight
Dimension - Bolt Hole Size inch	0.39 in
Dimension - Bolt Size fraction	3/8
Dimension - Bolt Size inch	0.38
Dimension - Length Overall inch	4.36 in
Dimension - N inch	0.50 in

### General

Die Index	24
Trade Name	HYLUG™
Sub Brand	HYLUG
Color Code	Black
Physical Attribute - Tongue Type	Standard
Plated	Y
Feature - Barrel Type	Standard
Feature - Barrel Style	Chamfered;Skived
Type	Standard Barrel, Tin Plated
UPC 12 Digit	781810018132
UPC 14 Digit GTIN	00781810018132
Material	COPPER
Plating Type	Tin - Electro Plated
Finish Type	Tin-Plated
UPC	781810018132

## Logistics

Minimum Pack Quantity	1
Carton Quantity	6

## Product Assets

- [Catalog \[English\]](#)
- [Installation Manual \[English\]](#)
- [Installation Manual \[French, English\]](#)



A Hubbell brand