



BURNDY Catalog Number	YA3CLB
UPC Number	781810501306
Description	BELLUG 3STR/4FX-5/16 STD
Status	Active

Web Use
BURNDY Product Line

Dimensional	
Tongue Angle	Straight
Length (in)	1.92
Tongue Type	Standard
Barrell Style	Belled
Bolt Hole Size (in)	0.33
Barrel Type	Standard
Thickness	0.09
B Length (in)	0.88
Pad Width (in)	0.55
Strip Length	15/16
General	
Number of Holes	1
Product Description	Cu Comp Terminal Flex Cond, 1 Hole/W/InspWindow, 3 Str Code, N50 Navy, 4 Flex, 4(105/#24)DLO, 600 V-35 kV, 5/16" Stud, Belled End
Conductor(s)	
Aircraft Cable Size (Range)	N/A
Flex (Class H) Size - Range	4 AWG
Flex (Class I) Size - Range	4 AWG
Copper Solid Size (Range)	N/A
DLO Size (Range)	4 (105/#24) DLO
Navy Cable Size (Range)	50 (19) Navy
Copper Stranded (Range)	3 AWG
Flex (Class G) Size - Range	4 AWG
Flex (Class M) Size - Range	4 AWG
Physical	
Type of Plating	Tin - Electro Plated
Bolt Hole Size	5/16
Color Code	White
Plated (Yes or No)	Y
Index Number	9,1016
Product Material	Copper
Approvals / Certifications	
UL Listed	Y
CSA Certified	Y
ROHS Compatible	Compliant
UL Recognized	N
CULUS	N
Industry Standards	UL468A-468B
Documentation	

For further technical assistance, please contact us

BURNDY LLC - USA

47, industrial Park Drive
Manchester NH03109

BURNDY Technical Services

47, industrial Park Drive
Manchester NH03109

Hours: 8.00 AM - 5.00 PM

Monday - Friday

Phone: 000-346-4175