



**BURNDY Catalog Number**  
**UPC Number**  
**Description**  
**Status**

YA3CLB  
 7818105013066  
 BELLUG 3STR/4FX-5/16 STD  
 Active

**Web Use**  
 BURNDY Product Line

**Dimensional**

Tongue Angle	Straight
Length (in)	1.92
Tongue Type	Standard
Barrell Style	Belled
Bolt Hole Size (in)	0.33
Barrel Type	Standard
Thickness	0.09
B Length (in)	0.88
Pad Width (in)	0.55
Strip Length	15/16

**General**

Number of Holes	1
Product Description	Cu Comp Terminal Flex Cond, 1 Hole/W/InspWindow, 3 Str Code, N50 Navy, 4 Flex, 4(105/#24)DLO, 600 V-35 kV, 5/16" Stud, Belled End

**Conductor(s)**

Aircraft Cable Size (Range)	N/A
Flex (Class H) Size - Range	4 AWG
Flex (Class I) Size - Range	4 AWG
Copper Solid Size (Range)	N/A
DLO Size (Range)	4 (105/#24) DLO
Navy Cable Size (Range)	50 (19) Navy
Copper Stranded (Range)	3 AWG
Flex (Class G) Size - Range	4 AWG
Flex (Class M) Size - Range	4 AWG

**Physical**

Type of Plating	Tin - Electro Plated
Bolt Hole Size	5/16
Color Code	White
Plated (Yes or No)	Y
Index Number	9,1016
Product Material	Copper

**Approvals / Certifications**

UL Listed	Y
CSA Certified	Y
ROHS Compatible	Compliant
UL Recognized	N
CULUS	N
Industry Standards	UL468A-468B

**Documentation**

For further technical assistance, please contact us

**BURNDY LLC - USA**

47 East Industrial Park Drive  
 Manchester NH 03109

**BURNDY Technical Services**

47 East Industrial Park Drive  
 Manchester NH 03109

Hours: 8:00 AM - 5:00 PM  
 Monday - Friday  
 Phone: 800-346-4175