

## YA8CA3, Compression Terminal, 8 AWG Al, 1-Hole, 1/4" Stud

By Burndy  
Catalog # [YA8CA3](#)

8 AWG, AL, 1 Hole, 1/4" Stud, AL9CU



### Features

- UL486A-486B Listed and CSA Certified
- Aluminum terminals are dual rated to accommodate both copper and aluminum wire and are indicated with AL-CU on the connector - AL9CU is UL Listed 90°C, up to 35kV, AL7CU is UL Listed 75°C, up to 35kV
- Barrel is designed with an internal chamfer at the wire entry to ensure smooth insertion of the wire, preventing possible damage of the wire strands during insertion
- Electro-tin plated unless otherwise specified to reduce galvanic corrosion (bimetallic) and resist corrosive elements
- Connectors are clearly marked with wire size, die index, color code, and crimp location bands
- Factory pre-filled with PENETROX Type A13 oxide inhibitor
- Color coded end caps are factory inserted in the barrels to match the die color code and prevent foreign materials from entering the barrel
- Aluminum oxidation is not easily detected but causes resistance in a connection, it is imperative the proper preparation takes place prior to making an aluminum-to-aluminum connection

### Application

Wire Termination

### Specifications

Buy American Compliant	No
Certification - cULus	No
EU RoHS Indicator	Yes
Certification - UL Recognized	No
Industry Standard(s)	UL 486A-486B
Certification - ETL	No
Standards - Industry Standards Met	UL 486A-486B
Standards - RoHS Compliance Status	CM
Certification - CSA Approved	Yes
UL Listed	Yes

### Conductor

Conductor - Material	ALUMINUM / COPPER
Wire Size	8 AWG
Conductor - Copper Str Size	8 AWG
Conductor - AL Str Size	8 AWG
Conductor - AL Str Size Range	8 AWG

Conductor Size	8 AWG
Conductor - Copper Str Size Range	8 AWG
Conductor Type	CODE

### Configuration

Physical Attribute - Number of Holes	1
Connector Type	DUAL RATED

### Current

Voltage - Maximum	35000
Voltage Rating	35 kV

### Dimensions

Dimension - Outside Diameter inch	0.30 in
Dimension - L Length Overall mm	42 mm
Dimension - Pad Width inch	0.53 in
Dimension - Hole Size fraction	1/4
Dimension - Hole Size inch	0.27
Dimension - Hole Size mm	6.9 mm
Dimension - Strip Length inch	5/8
Dimension - Stud Size fraction	1/4
Dimension - Stud Size inch	1/4
Dimension - B Length fraction	5/8 in
Dimension - B Length inch	0.62 in
Dimension - Z inch	0.50 in
Physical Attribute - Tongue Angle	Straight
Dimension - Bolt Hole Size inch	0.27 in
Dimension - Bolt Size fraction	1/4
Dimension - Bolt Size inch	0.25
Dimension - Length Overall inch	1.65 in
Dimension - D inch	0.75 in
Dimension - N inch	0.25 in

### General

Die Index	374
Trade Name	HYLUG™
Sub Brand	HYLUG
Color Code	Blue

Physical Attribute - Tongue Type	Standard
Plated	Y
Feature - Barrel Type	Standard
Type	YA-A, Dual Rated
UPC 12 Digit	781810752401
UPC 14 Digit GTIN	00781810752401
Material	ALUMINUM
Plating Type	Tin - Electro Plated
Finish Type	Tin-Plated
UPC	781810752401

### Logistics

Minimum Pack Quantity	1
Carton Quantity	20

### Operational

Temperature Rating	194
--------------------	-----

### Product Assets

[Catalog \[English\]](#)

[Installation Manual \[English\]](#)

[Installation Manual \[English\]](#)



A Hubbell brand