



## YAES10N12, Nylon Ring Terminal For 12 - 10 AWG

By Burndy  
Catalog # [YAES10N12](#)

Fork Tongue Copper terminal, 12-10, Max. Insul.Dia. Accom.: .209,  
Color Code: Yellow, 8-10, 1.12 in L, .37 in W, Tin Plated, 600 Volts  
Max.

### Features

- Integral one-piece copper barrel / insulation grip and wire strain relief design for improved physical strength characteristics over a multi-piece design
- Manufactured of pure electrolytic copper for maximum conductivity, low resistance and ductility for excellent crimp forming properties
- Brazed seam provides a stronger barrel design, minimizes any possible splitting and eliminates folding
- Deep inner barrel serrations and smooth funnel entry for excellent conductivity and pullout strength values along with easy wire insertion
- Insulation is locked in place, will not twist off, maintaining proper dielectric values
- Electro-tin plated for durable, long lasting resistance to corrosion
- Color-coded and clearly marked for quick, easy wire size identification
- Ring tongue provides a secure termination under the screw head that cannot be removed without complete removal of the screw, allowing two or more terminals to be stacked on a common stud

### Application

For use on copper compression connections

### General

Catalog Number	YAES10N12
Color Code	Yellow
Connector Type	Ring Terminal
EU RoHS Indicator	Yes
Feature - Barrel Style	Skived
Insulation	Y
Insulation Type	Nylon
Material	Copper
Military Specification	MS25036
Physical Attribute - Number of Holes	1
Physical Attribute - Tongue Type	Ring
Plated	Y
Plating Type	Tin



Sub Brand	INSULUG
Trade Name	INSULUG™
Type	YAES
UPC	781810805053
UPC 14 Digit GTIN	00781810805053

### Dimensions

Dimension - Bolt Size fraction	#10
Dimension - G inch	0.2 in
Dimension - Hole Size inch	0.203 in
Dimension - Length Overall inch	1.12 in
Dimension - Pad Width inch	0.37 in
Dimension - Strip Length inch	11/32 in
Dimension - Stud Size inch	#10

### Electrical Ratings

Voltage - Maximum	600 V
-------------------	-------

### Conductor Related

Conductor - Copper Str Size	12 AWG;10 AWG
Conductor - Copper Str Size Range	12 AWG-10 AWG
Conductor Size	12 - 10 AWG
Conductor Type	CU C Str-Size

### Certifications And Compliance

Buy America(n) Qualified	TAA Compliant (All status valid till December 2024)
Certification - ETL	No
Certification - UL Recognized	No
Certification - cULus	No
Industry Standard(s)	<ul style="list-style-type: none"><li>• UL486</li><li>• Military Specified (Mil-Spec)</li></ul>
Standards - Industry Standards Met	UL486
Standards - RoHS Compliance Status	CM
UL Listed	Yes

### Logistics

Carton Quantity 500  
Minimum Pack Quantity 500  
Pallet Quantity 99999

**Product Assets**

[3D Models - YAES10N12\\_MODEL-STEP](#)  
[3D Models - YAES10N12\\_MODEL-IGES](#)

[3D Models - YAES10N12\\_MODEL-PDF](#)  
[Catalogs - BURNDY Master Catalog - Section B - Small Terminals](#)  
[Catalogs - BURNDY Master Catalog - Full Line BURNDY Catalog](#)  
[Interactive Catalog - BURNDY Full-Line Digital Catalog](#)  
[Product Cross Section Image\(s\) - BUR\\_YAES10N11\\_LineArt](#)  
[Sales Drawings - 50094155](#)  
[Specifications - YAES10N12](#)



A Hubbell brand

©2025 Hubbell Incorporated. All rights reserved  
BRDY-YAES10N12-SPEC-EN | REV 7/2025