


# YAV10T4, Uninsulated Ring Terminal For 12 - 10 AWG, 1-Hole, 3/8" Stud

By Burndy  
Catalog # [YAV10T4](#)



Copper Compression Lug, 1 Hole w/ Inspection Window, 14-10 AWG/12-10 AWG, 3/8" Stud, Short Barrel, Tin Plated.

## Features

- Manufactured from seamless pure electrolytic copper tubing to provide maximum conductivity, low resistance and excellent ductility for crimping
- Seamless tubular crimp barrel design - No seams to split resulting in a very high quality electrical connection, also can be used on solid conductor
- Double thick tongue structurally a very strong terminal tongue
- Produced from tubular copper, extra copper material assures the compression connector will operate cooler than the conductors it connects
- Internally bevelled barrel for easy cable entry, especially for flexible conductors
- Inspection hole provides easy visual check for proper conductor insertion
- Electro-tin plated for a long lasting durable corrosion resistance

## Application

Industrials, Hospitals, Utilities, Marine, Computer

## General

Application - For Use On	Copper Commercial (Code) Cable, Type AN Aircraft Cable, Extra Flexible Conductors
Catalog Number	YAV10T4
Connector Type	Ring Terminal
EU RoHS Indicator	Contact Manufacturer
Feature - Barrel Style	Chamfered
Feature - Barrel Type	Standard
Material	Copper
Military Specification	AS20659
Physical Attribute - Number of Holes	1
Physical Attribute - Tongue Type	Ring
Plated	Y
Plating Type	Tin - Electro Plated
Sub Brand	HYLUG
Trade Name	HYLUG™
Type	Ring Tongue

UPC 781810025284  
UPC 14 Digit GTIN 00781810025284

## Dimensions

Dimension - B Length fraction	3/8 in
Dimension - B Length inch	0.45 in
Dimension - Bolt Size fraction	3/8
Dimension - D inch	0.63 in
Dimension - Length Overall inch	1.17 in
Dimension - N inch	0.28 in
Dimension - Outside Diameter inch	0.21 in
Dimension - Pad Width inch	0.56 in
Dimension - Stud Size inch	3/8

## Conductor Related

Conductor - Copper Solid Size	12 AWG;11 AWG;10 AWG
Conductor - Copper Solid Size Range	12 AWG-10 AWG
Conductor - Copper Str Size	12 AWG;10 AWG
Conductor - Copper Str Size Range	12 AWG-10 AWG
Conductor Size	12 - 10 AWG
Conductor Type	<ul style="list-style-type: none"> <li>• CU C Solid-Size</li> <li>• CU C Str-Size</li> </ul>

## Certifications And Compliance

Buy America(n) Qualified	Contact Manufacturer
Certification - ETL	No
Certification - UL Recognized	No
Certification - cULus	No
Industry Standard(s)	<ul style="list-style-type: none"> <li>• UL467</li> <li>• Military Specified (Mil-Spec)</li> </ul>
Standards - Industry Standards	UL486
Standards - Industry Standards Met	
Standards - RoHS Compliance	CM
Status	
UL Listed	Yes

## Logistics

Carton Quantity 500  
Minimum Pack Quantity 500  
Pallet Quantity 99999

**Product Assets**

3D Models - YAV10T4\_MODEL-STEP  
3D Models - YAV10T4\_MODEL-PDF  
3D Models - YAV10T4\_MODEL-IGES  
Catalogs - BURNDY Master Catalog - Section B - Small Terminals

Catalogs - BURNDY Master Catalog - Full Line BURNDY Catalog  
Installation Manuals - Medium & Large HYDENT Copper & Aluminum Terminal Crimp Instructions with 750 Series 12-Ton Tool  
Installation Manuals - Copper Code Standard Terminals Tooling and Installation Instructions  
Interactive Catalog - BURNDY Full-Line Digital Catalog  
Product Cross Section Image(s) - BUR\_YAV18T5\_LineArt  
Sales Drawings - 50094160  
Specifications - YAV10T4



A Hubbell brand