

YAV26L2TC38FX, Cu Compression, 2-Hole, 3/8" Stud, 1" Spacing, Standard Barrel, 2/0 Flex

By Burndy
Catalog # [YAV26L2TC38FX](#)

2/0 Flex G,H,I,K,M,DLO, 2/0 AWG, CU, 2 Hole, 3/8 Stud, 1 IN Spacing, Standard Barrel, Inspection Window



Features

- Electro-tin plated unless otherwise specified to reduce galvanic corrosion (bimetallic) and resist corrosive elements
- Connectors are clearly marked with stamping and barrel color coding
- For applications greater than 2000 Volts consult cable manufacturer for voltage stress relief instructions

Application

Wire Termination

Specifications

Buy American Compliant	No
Certification - cULus	No
EU RoHS Indicator	Yes
Certification - UL Recognized	No
Industry Standard(s)	UL 486A-486B
Certification - ETL	No
Standards - RoHS Compliance	CM
Status	
Certification - CSA Approved	Yes
UL Listed	Yes

Conductor

Conductor - Material	COPPER
Wire Size	2/0 AWG
Conductor - Copper Str Size	"2/0 AWG"
Conductor - Copper Flex I Size Range	2/0 AWG
Conductor - Copper Flex K Size	"2/0 AWG"
Conductor - Copper Flex K Size Range	2/0 AWG
Conductor - Copper Flex M Size	"2/0 AWG"
Conductor - Copper Flex M Size Range	2/0 AWG
Conductor - Copper Solid Size	2/0 AWG
Conductor - Copper Solid Size Range	2/0 AWG
Conductor - Copper Str Compact Size	"2/0 AWG"
Conductor - Copper DLO Size	2/0 AWG
Conductor - Copper DLO Size Range	2/0 AWG
Conductor - Copper Flex G Size	"2/0 AWG"

Conductor - Copper Str Navy Size	125
Conductor - Copper Flex G Size Range	2/0 AWG
Conductor - Copper Str Navy Size Range	125 (61) Navy
Conductor - Copper Flex H Size	"2/0 AWG"
Conductor Size	2/0 AWG
Conductor - Copper Str Size Range	2/0 AWG
Conductor - Copper Flex H Size Range	2/0 AWG
Conductor Type	CODE/FLEX
Conductor - Copper Flex I Size	"2/0 AWG"
Conductor - CopperWeld Str Size	2/0 WELD
Conductor - CopperWeld Str Size Range	2/0 WELD

Configuration

Physical Attribute - Number of Holes	2
Connector Type	STANDARD BARREL

Current

Voltage - Maximum	35000
Voltage Rating	35 kV

Dimensions

Dimension - Outside Diameter inch	0.63 in
Dimension - L Length Overall mm	79 mm
Dimension - Pad Width inch	0.93 in
Dimension - Hole Size fraction	3/8
Dimension - Hole Size inch	0.41
Dimension - Hole Size mm	10.4 mm
Dimension - Strip Length inch	13/16 in
Dimension - Stud Size fraction	3/8
Dimension - B Length fraction	13/16 in
Dimension - B Length inch	0.81 in
Dimension - Z inch	0.43 in
Physical Attribute - Tongue Angle	Straight
Dimension - Bolt Hole Size inch	0.41 in

Dimension - Bolt Size fraction 3/8
Dimension - Bolt Size inch 0.38
Dimension - Length Overall inch 3.12 in
Dimension - N inch 0.41 in

General

Die Index 13
Trade Name HYLUG™
Sub Brand HYLUG
Color Code Black
Physical Attribute - Tongue Type Standard
Plated Y
Feature - Barrel Type Standard
Feature - Barrel Style Chamfered;Skived
Type Standard Barrel, Tin Plated
UPC 12 Digit 781810021767

UPC 14 Digit GTIN 00781810021767
Material COPPER
Plating Type Tin
Finish Type Tin-Plated
UPC 781810021767

Logistics

Minimum Pack Quantity 1
Carton Quantity 100
Pallet Quantity 18500

Operational

Temperature Rating 194

Product Assets

[Catalog \[English\]](#)
[Installation Manual \[English\]](#)
[Installation Manual \[English\]](#)



A Hubbell brand