



YAV28LNT38FX, Cu Compression, 1-Hole, 3/8" Stud, Standard Barrel, Narrow Tongue, 4/0 Flex

By Burndy

Catalog # [YAV28LNT38FX](#)

4/0 Flex G,H,I,K,M,DLO, 4/0 AWG, CU, 1 Hole, 3/8 Stud, Standard Barrel, Inspection Window, Narrow Tongue

Features

- Electro-tin plated unless otherwise specified to reduce galvanic corrosion (bimetallic) and resist corrosive elements
- Connectors are clearly marked with stamping and barrel color coding
- For applications greater than 2000 Volts consult cable manufacturer for voltage stress relief instructions

Application

Wire Termination

Specifications

Buy American Compliant	Contact Manufacturer
Certification - cULus	No
EU RoHS Indicator	Yes
Certification - UL Recognized	No
Industry Standard(s)	UL 486A-486B
Buy America(n) Qualified	Contact Manufacturer
Certification - ETL	No
Standards - RoHS Compliance Status	CM
Certification - CSA Approved	Yes
UL Listed	Yes

Conductor

Conductor - Material	COPPER
Wire Size	4/0 AWG
Conductor - Copper Str Size	"4/0 AWG"
Conductor - Copper Flex I Size Range	4/0 AWG
Conductor - Copper Flex K Size	"4/0 AWG"
Conductor - Copper Flex K Size Range	4/0 AWG
Conductor - Copper Flex M Size	"4/0 AWG"
Conductor - Copper Str Compact Size	"4/0 AWG"
Conductor - Copper DLO Size	4/0 AWG
Conductor - Copper DLO Size Range	4/0 AWG
Conductor - Copper Flex G Size	"4/0 AWG"
Conductor - Copper Str Navy Size	200
Conductor - Copper Flex G Size Range	4/0 AWG



Conductor - Copper Flex H Size	"4/0 AWG"
Conductor Size	4/0 AWG
Conductor - Copper Str Size Range	4/0 AWG
Conductor - Copper Flex H Size Range	4/0 AWG
Conductor Type	CODE/FLEX
Conductor - Copper Flex I Size	"4/0 AWG"
Conductor - CopperWeld Str Size	4/0 E AWG;4/0 EK AWG;4/0 F AWG;4/0 G AWG;4/0 V AWG

Configuration

Physical Attribute - Number of Holes	1
Connector Type	STANDARD BARREL

Current

Voltage - Maximum	35000
Voltage Rating	35 kV

Dimensions

Dimension - Outside Diameter inch	0.77 in
Dimension - L Length Overall mm	61 mm
Dimension - Pad Width inch	0.94 in
Dimension - Hole Size fraction	3/8
Dimension - Hole Size inch	0.41
Dimension - Hole Size mm	10.4 mm
Dimension - Strip Length inch	1-1/16
Dimension - Stud Size fraction	3/8
Dimension - Stud Size inch	3/8
Dimension - B Length fraction	1 in
Dimension - B Length inch	1.03 in
Dimension - Z inch	0.42 in
Physical Attribute - Tongue Angle	Straight
Dimension - Bolt Hole Size inch	0.39 in
Dimension - Bolt Size fraction	3/8
Dimension - Bolt Size inch	0.38
Dimension - Length Overall inch	2.42 in
Dimension - N inch	0.41 in

General

Die Index	15
Trade Name	HYLUG™
Sub Brand	HYLUG,TERMINALS
Color Code	Purple
Plated	Y
Feature - Barrel Type	Standard
Feature - Barrel Style	Chamfered
Type	YAV-L-NTFX, Standard Barrel
UPC 14 Digit GTIN	00781810343678
Material	COPPER
Plating Type	Tin - Electro Plated
Finish Type	Tin-Plated

UPC781810343678

Logistics

Minimum Pack Quantity	50
Carton Quantity	50
Pallet Quantity	17400

Product Assets

- Catalog [English]
- Installation Manual [English]
- Installation Manual [English]



A Hubbell brand