



Compression Terminal

By Burndy
Catalog # [YAV28TC12FXB](#)

4/0 Flex G,H,I,K,M,DLO, 4/0 AWG CU, One Hole, 1/2 Stud Size, Long Barrel, Bell End, Tin Plated, UL/CSA, 90°C, Up to 35kV, Purple Color Code, 15 Die Index.



Application

Wire Termination

General

| | |
|--------------------------------------|-------------------------|
| Catalog Number | YAV28TC12FXB |
| Color Code | Purple |
| Connector Type | LONG BARREL |
| Die Index | 15 |
| EU RoHS Indicator | Yes |
| Feature - Barrel Style | Belled |
| Feature - Barrel Type | Long |
| Finish Type | Tin-Plated |
| Material | COPPER |
| Physical Attribute - Number of Holes | 1 |
| Physical Attribute - Tongue Type | Standard |
| Plated | Y |
| Plating Type | Tin - Electro Plated |
| Sub Brand | HYLUG |
| Trade Name | HYLUG™ |
| Type | Long Barrel, Tin Plated |
| UPC | 781810044636 |
| UPC 12 Digit | 7818100446366 |

Dimensions

| | |
|-----------------------------------|----------|
| Dimension - B Length fraction | 1-3/4 in |
| Dimension - B Length inch | 1.77 in |
| Dimension - Bolt Hole Size inch | 0.52 in |
| Dimension - Bolt Size fraction | 1/2 |
| Dimension - Bolt Size inch | 0.5 |
| Dimension - Hole Size fraction | 1/2 |
| Dimension - Hole Size inch | 0.56 |
| Dimension - Hole Size mm | 14 mm |
| Dimension - L Length Overall mm | 92 mm |
| Dimension - Length Overall inch | 3.63 in |
| Dimension - N inch | 0.62 in |
| Dimension - Outside Diameter inch | 0.77 in |
| Dimension - P inch | 2.29 in |
| Dimension - Pad Width inch | 1.14 in |
| Dimension - Strip Length inch | 1-7/8 |

Conductor Related

| | |
|--------------------------------------|-----------|
| Conductor - Copper DLO Size | 4/0 AWG |
| Conductor - Copper DLO Size Range | 4/0 AWG |
| Conductor - Copper Flex G Size | "4/0 AWG" |
| Conductor - Copper Flex G Size Range | 4/0 AWG |
| Conductor - Copper Flex H Size | "4/0 AWG" |
| Conductor - Copper Flex H Size Range | 4/0 AWG |
| Conductor - Copper Flex I Size | "4/0 AWG" |
| Conductor - Copper Flex I Size Range | 4/0 AWG |
| Conductor - Copper Flex K Size | "4/0 AWG" |
| Conductor - Copper Flex K Size Range | 4/0 AWG |
| Conductor - Copper Flex M Size | "4/0 AWG" |
| Conductor - Copper Str Compact Size | "4/0 AWG" |
| Conductor - Copper Str Navy Size | 200 |
| Conductor - Copper Str Size | "4/0 AWG" |
| Conductor - Copper Str Size Range | 4/0 AWG |
| Conductor - Material | COPPER |
| Conductor Size | 4/0 AWG |
| Conductor Type | CODE/FLEX |
| Wire Size | 4/0 AWG |

Certifications And Compliance

| | |
|------------------------------------|--------------|
| Certification - CSA Approved | Yes |
| Certification - ETL | No |
| Certification - UL Recognized | No |
| Certification - cULus | No |
| Industry Standard(s) | UL 486A-486B |
| Standards - Industry Standards Met | UL 486A-486B |
| Standards - RoHS Compliance Status | CM |
| UL Listed | Yes |

Logistics

| | |
|-----------------------------------|----------|
| Dimension - Stud Size fraction | 1/2 |
| Dimension - Stud Size inch | 1/2 |
| Dimension - Thread Size | 1/2 |
| Dimension - Z (inch) | 0.64 in |
| Physical Attribute - Tongue Angle | Straight |

Electrical Ratings

| | |
|-------------------|-------|
| Voltage - Maximum | 35000 |
| Voltage Rating | 35 kV |

| | |
|-----------------------|----|
| Carton Quantity | 25 |
| Minimum Pack Quantity | 1 |

Product Assets

[Catalogs - Full Line BURNDY Catalog](#)
[Catalogs - Section C - Compression Connections](#)
[Customer Notices - Prop 65 Notice](#)
[Installation Manuals - Copper Flex Long Terminals Tooling and Installation Instructions](#)
[Sales Drawings - SE208075](#)
[Video - HYDENT Compression Terminal Overview Video](#)



A proud member of the Hubbell Family.

©2024 Hubbell Incorporated. All rights reserved.
BRDY-YAV28TC12FXB-SPEC-EN | REV 6/2024